

County Surveyor's Record, Douglas County, Oregon

-11-

CHAINS	Ascend 204 ft. over broken SE. slope, changing to E. slope.
28.85	Spur, ridge, bears N. 40° E. and S. 40° W.; desc. 20 ft. along broken general W. slope.
38.28	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\frac{1}{4}$ S 21/S 22 T 21 S R 11 W 1960
	from which
	A cedar, 5 ins. diam., bears S. 67° E., 8 lks. dist., mkd. $\frac{1}{4}$ S22 BT.
	A fir, 48 ins. diam., bears S. 67° W., 51 lks. dist., mkd. $\frac{1}{4}$ S21 BT.
	Ascend 158 ft. over broken SW. slope, changing to S. slope.
51.45	Ridge, divide between Otter Creek and Brainard Creek, bears NE. and SW.; desc. 223 ft. over broken NE. slope, changing to E. slope.
57.42	Point for the N 1/16 sec. cor. of secs. 21 and 22.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	N 1/16 S 21/S 22 1960
	from which
	A maple, 15 ins. diam., bears N. $43\frac{1}{2}$ ° E., 103 lks. dist., mkd. N 1/16 S22 BT.
	A fir, 15 ins. diam., bears S. 20° W., 101 lks. dist., mkd. N 1/16 S21 BT.
	Descend 178 ft. along broken E. slope.
71.20	Ravine, course N. 60° E.; asc. 39 ft. along E. slope.
74.60	Spur, slopes N. 40° E.; desc. 93 ft. over NW. slope.
76.56	The cor. of secs. 15, 16, 21, and 22, monumented with an iron post, $2\frac{1}{2}$ ins. diam., projecting 4 ins. above ground, marked and witnessed as described in the official record.
	Land, mountainous Soil, sandy clay loam. Timber, fir, cedar, hemlock, maple, alder, and chinquapin; undergrowth, vine maple, salmonberry, coast huckleberry, red huckleberry, hazel, arrowwood, ceanothus, salal, and fern.
	From the cor. of secs. 14, 15, 22, and 23.
	S. 89° 17' W., bet. secs. 15 and 22.