

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 21 S., R. 11 W.

CHAINS	<p>Descend 27 ft. over SW. slope, through heavy timber and dense undergrowth.</p> <p>0.80 Ravine, course S.; asc. 71 ft. over SE. slope.</p> <p>3.85 Top of ascent, slopes S.; desc. 393 ft. over broken SW. slope.</p> <p>19.75 Branch, 3 lks. wide, course N. 40° W.; asc. 19 ft. over NE. slope.</p> <p>19.97 Point for the E 1/16 sec. cor. of secs. 15 and 22.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 $\frac{S\ 15}{S\ 22}$ 1960</p> <p>from which</p> <p style="padding-left: 40px;">An alder, 10 ins. diam., bears N. 17¼° W., 54 lks. dist., mkd. E 1/16 S15 BT.</p> <p style="padding-left: 40px;">An alder, 17½ ins. diam., bears S. 68½° E., 120 lks. dist., mkd. E 1/16 S22 BT.</p> <p>Ascend 259 ft. over broken NE. slope.</p> <p>31.00 Spur, slopes N. 25° E.; desc. 300 ft. over NW. slope.</p> <p>38.60 Dry branch, 3 lks. wide, course N. 10° E.; asc. 63 ft. over E. slope.</p> <p>39.94 Point for the ¼ sec. cor. of secs. 15 and 22 at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.</p> <p style="text-align: center;">¼ $\frac{S\ 15}{S\ 22}$ FOOK PER WOBBE T 21 S R 11 W 5-87 M104-43A4B 1960</p> <p>from which</p> <p style="padding-left: 40px;">A maple, 38 ins. diam., bears N. 87° E., 45 lks. dist., mkd. ¼ S15 BT.</p> <p style="padding-left: 40px;">A cedar, 40 ins. diam. bears S. 23½° W., 270 lks. dist., mkd. ¼ S22 BT.</p> <p>Ascend 234 ft. over broken NE. slope.</p> <p>46.50 Spur, slopes N. 50° E.; desc. 133 ft. over N.W. slope.</p> <p>49.00 Ravine, course N. 10° E.; asc. 229 ft. over broken NE. slope.</p> <p>55.80 Spur, slopes N. 15° W.; desc. 202 ft. over SW. slope.</p> <p>59.91 Point for the W 1/16 sec. cor. of secs. 15 and 22.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 $\frac{S\ 15}{S\ 22}$ 1960</p> <p>from which</p>
--------	--