

County Surveyor's Record, Douglas County, Oregon

-14-

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 21 S., R. 11 W.

CHAINS

75.00 Spur, slopes N. 20° W.; desc. 70 ft. over W. slope.

78.70 The cor. of secs. 20, 21, 28, and 29, determined at record bearing and distance from the original bearing tree:

A maple, 63 ins. diam., bears S. 87½° W., 511 lks. dist., with a healed blaze.

At the corner point.

Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins in the ground, to solid rock and supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 21	S R	11 W
S 20	S 21	
S 29	S 28	
1960		

*FD. OK 2/84
J. PRUCHANAU
M 96-63 A-B*

From which new bearing trees:

A fir, 29 ins. diam., bears N. 1° E., 55 lks. dist., mkd. T21S R11W S21 BT.

A cedar, 10 ins. diam., bears S. 56½° E., 41 lks. dist., mks. T21S R11W S28 BT.

A cedar, 10 ins. diam., bears S. 9° W., 66 lks. dist., mkd. T21S R11W S29 BT.

A fir, 11 ins. diam., bears N. 28½° W., 75 lks. dist., mkd. T21S R11W S20 BT.

Land, mountainous.

Soil, sandy clay loam with silt in the Otter Slough bottom.

Timber, fir, hemlock, cedar, alder, and maple; undergrowth, vine maple, salmonberry, coast huckleberry, red huckleberry, salal, cat tails, and fern.

Subdivision of Section 22, T. 21 S., R. 11 W.

The following subdivision of section 22 was executed in conformity with legal surveying practice. Only the true line field notes are given herein.

From the ¼ sec. cor. of secs. 22 and 27.

N. 2° 01' W., on the N. and S. center line of sec. 22, marking and blazing the true line.

Ascend 35 ft. over gentle SE. slope, over open land.

7.60 Dry creek, 3 lks. wide, course S. 10° E.; asc. 100 ft. along W. slope.

19.80 Point for the center S 1/16 sec. cor. of sec. 22.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16	C	S 22
	C	
1960		