


County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the S. Bdy., T.19S., R.8W.

CHAINS

- 1.60 Dry draw, course SE.; ascend 201 ft. over NE. slope.
- 5.90 Top of spur, slopes SE.; descend 181 ft. over gradual SW. slope.
- 19.14 Bottom of draw, a little seepage water, course S.; thence along a broken S. slope.
- 26.40 A low spur, slopes S.; descend 116 ft. along broken S. slope, to Esmond Creek.
- 27.17 Ravine, a little seepage water, course S.
- 29.43 Low spur, slopes S.
- 34.60 Esmond Creek, 15 lks. wide, course N. 70° W.; thence over bottom land.
- 36.50 Esmond Creek, 15 lks. wide, course N. from N. 80° E.
- 37.40 Leave bottom land and ascend 76 ft. over NE. slope.
- 39.83 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the orig. corner.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, with brass cap mkd.




from which

A fir, 32 ins. diam., bears N. 49° E., 80 lks. dist., mkd. $\frac{1}{4}$ S 36 BT.

A fir, 12 ins. diam., bears S. 26 $\frac{1}{2}$ ° W., 67 lks. dist., mkd. $\frac{1}{4}$ S 1 BT.

- 43.90 Top of spur, slopes N.; descend 43 ft. over NW. slope.
- 45.60 Bottom of dry draw, course NE.; ascend 155 ft. over E. slope.
- 49.10 Top of spur, slopes NE.; descend 228 ft. over NW. slope.
- 56.30 Bottom of dry ravine, course NE.; ascend 568 ft. to sec. cor., along broken SE. slope.
- 64.30 Sidehill drain, course SE.
- 71.20 Ravine, course NE.
- 79.66 The point for the cor. of secs. 1, 2, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd.



from which

A fir, 22 ins. diam., bears N. 52° E., 23 lks. dist., mkd. T19S R8W S36 BT.