

County Surveyor's Record, ⁷ Douglas County, Oregon

Dependent Resurvey of a Portion of the S. bdy. of T. 19 S., R. 8 W.

CHAINS

- 2.20 Top of low spur, slopes SE.; descend slightly over SW. slope.
- 5.15 Dry draw, course SE.; ascend 247 ft. over E. slope.
- 11.30 Top of ridge, bears N. and S.; descend 319 ft. over W. slope.
- 21.60 Dry draw, drains NW.; ascend 46 ft. over E. slope.
- 23.40 A spur, slopes N.; descend 18 ft.
- 24.80 Bottom of dry ravine, course NE.; ascend 138 ft. over steep E. slope.
- 27.80 Top of spur, slopes NW.; descend 244 ft. along SW. slope.
- 39.47 Point of the cor. of secs. 4, 5, 32 and 33, as determined from the original bearing trees:

A fir, 31 ins. diam., bears N. 51° E., 43 lks. dist. with healed blaze facing SW.


A fir, 31 ins. diam., bears S. 16½° E., 29 lks. dist., with healed blaze facing NW.

A stump hole of a fir bears S. 51° W., 27 lks. dist.

A fir, 25 ins. diam., bears N. 16½° W., 47 lks. dist., with healed blaze facing SE.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd.



from which

A fir, 24 ins. diam., bears S. 6° 45' W., 51 lks. dist., mkd. T20S R8W S5 BT.

A fir, 30 ins. diam., bears N. 29° 45' W., 48 lks. dist. mkd. T19S R8W S32 BT.

Land, mountainous.

Soil, rocky clay.

Timber, heavy fir, hemlock, cedar, alder, chinquapin, maple, yew, and madrona.

Undergrowth, dense vine maple, salal, hazel, arrowwood, huckleberry, manzanita, poison oak and bracken.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 19 S., R. 8 W., Willamette Meridian, Oregon.

(Restoration of the 1891 survey of Charles M. Collier.)

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Twp.

N. 0° 20' E., bet. secs. 35 and 36, marking and blazing the true line.

Ascend 36 ft. over SE. slope; through heavy timber and dense undergrowth.