


County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivision, T. 19 S., R. 8 W.

CHAINS

- 1.50 Top of high spur, slopes NE.; descend 578 ft. over steep NW. slope
- 17.50 Bottom of dry ravine, course NE.; ascend 152 ft. over steep SE. slope.
- 26.50 Top of spur, slopes NE.; descend 272 ft. over NW. slope.
- 31.20 Foot of descent and south edge of an arm of Esmond Lake, bears E. and W.
- 32.95 N. edge of arm of Esmond Lake, bears NE. and SW.; ascend 67 ft. over SE. slope.
- 36.00 Top of low spur, slopes SE.; descend 13 ft. over NE. slope.
- 37.40 Bottom of short dry drain, course S. 70° E.; ascend 73 ft. over S. slope.
- 39.74 A fir, 17 ins. diam.
- 39.78 Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, with brass cap mkd.



from which

- A fir, 40 ins. diam., bears N. 5 $\frac{1}{2}$ ° W., 32 lks. dist., mkd. $\frac{1}{4}$ S35 BT.
- A fir, 17 ins. diam., bears S. 70 $\frac{1}{2}$ ° E., 13 lks. dist., mkd. $\frac{1}{4}$ S36 BT.

Ascend 80 ft. over SE. slope.

- 4 5.50 Top of spur, slopes N. 70° E.; descend 128 ft. over N. 20° E. slope.
- 51.80 Edge of Esmond Lake, bears N. 40° W. and S. 40° E.
(Note: The distance across Esmond Lake was obtained by offset and traverse on the random line.)
- 72.30 Edge of Esmond Lake, bears N. 20° E. and S. 20° W.; thence over bottom land on nearly level course.
- 74.20 Esmond Creek, 12 lks. wide, course N. 70° W.; ascend 45 ft. over rocky SW. slope.
- 79.56 Point for the cor. of secs. 25, 26, 35 and 36, marked with a cross (X) on the projecting corner of a boulder in place, 15x12x8 feet above ground; other marks indistinct.

At the corner point, under the projecting corner of the boulder

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

