

# County Surveyor's Record, Douglas County, Oregon


Dependent Resurvey of a Portion of the Subdivision, T. 19 S., R. 8 W.

CHAINS

A fir, 27 ins. diam., bears S.  $37\frac{1}{2}^{\circ}$  W., 45 lks. dist. showing a healed blaze facing NE. (Record, S.  $63^{\circ}$  W., 33 lks. dist.)

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap marked.



From which

A fir, 15 ins. diam., bears N.  $17^{\circ} 45'$  W., 70 lks. dist., mkd.  $\frac{1}{4}$  S 33 BT.

A fir, 30 ins. diam., bears S.  $46\frac{1}{4}^{\circ}$  E., 25 lks. dist., mkd.  $\frac{1}{4}$  S 34 BT.

N.  $0^{\circ} 08'$  W., beginning new measurement.

On nearly level course along W. slope.

- 3.30 Top of high spur, slopes N.  $20^{\circ}$  W., descend 36 ft. over NE. slope.
- 5.00 Head of dry ravine, course E.; ascend 67 ft. over SE. slope.
- 7.50 Top of spur, slopes NE.; descend 113 ft. over N. slope.
- 10.20 A dry draw, drains NE.; ascend 54 ft. over steep E. slope.
- 14.50 Top of spur, slopes NE.; descend 412 ft. over N. slope, changing to NE.
- 22.75 Stream, 1 lk. wide, course NE.; ascend 48 ft. over steep E. slope.
- 27.40 Top of spur, slopes NE.; descend 266 ft. over steep N. slope.
- 32.90 Esmond Creek, 10 lks. wide, course NW.; from NE.; ascend 61 ft. over S. slope.
- 39.30 An unimproved earth road, bears E. and S.  $80^{\circ}$  W.
- 39.63 The cor. of secs. 27, 28, 33 and 34, as determined from the original bearing trees:
  - A fir, 48 ins. diam., bears N.  $58^{\circ} 45'$  E., 79 lks. dist., showing a healed blaze facing SW.
  - A fir, 60 ins. diam., bears S.  $80\frac{1}{4}^{\circ}$  E., 42 lks. dist., showing a healed blaze facing W.
  - A fir, 40 ins. diam., bears S.  $12^{\circ}$  W., 108 lks. dist., with a healed blaze facing N.
  - A fir stump bears N.  $2\frac{1}{4}^{\circ}$  W., 53 lks. dist.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground with brass cap mkd.