


County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivision, T. 19 S., R. 8 W.

CHAINS



FD. OK 4/60
W. ELMSTAD
M. 84-77

from which

A fir, 8 ins. diam., bears N. 76° W., 64 lks. dist., mkd. T19S R8W S28 BT.

Land, mountainous.

Soil, rocky clay.

Timber, heavy fir, hemlock, cedar, alder, maple, chinquapin, dogwood, and madrona.

Undergrowth, dense vine maple, hazel, salmonberry, arrowwood, manzanita, rhododendron, and bracken.

From the cor. of secs. 26, 27, 34 and 35.

N. 89° 14' W., between secs. 27 and 34.

On nearly level course over bottom land; through heavy timber and very dense undergrowth.

2.20 An unimproved earth road, bears N. 75° E. and S. 75° W.

3.20 Leave bottom land, edge bears N. 75° E. and S. 60° W.; ascend 30 ft.

8.10 Top of ascent and end of spur sloping S.; descend 45 ft. over S. slope.

11.60 Unimproved road, bears NW. and SE.

17.80 Esmond Creek, 10 lks. wide, course N. 60° W.; ascend 36 ft. over NE. slope.

19.20 End of spur, from S. 20° W.; descend 10 ft. along N. slope.


30.00 A dry ravine, from the S.; ascend slightly.

30.50 End of spur, from the S.; descend 25 ft. along N. slope.

38.70 Esmond Creek, 15 lks. wide, course S. 80° W.

39.37 Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.



from which

An alder, 12 ins. diam., bears N. 8 1/2° W., 87 lks. dist., mkd. 1/4 S27 BT.

A Cedar 20 ins. diam., bears S. 24° E., 200 lks. dist., mkd. 1/4 S34 BT.

Over bottom land; through very dense undergrowth.

39.57 Esmond Creek, 15 lks. wide, course N. 80° W., from S. 70° E.