

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivision, T. 19 S., R. 8 W.

CHAINS

T19S	R8W
S 29	S 28
S 32	S 33
1952	

*FD. OK 9/80
W. EIMSTAD
M 89-77*

from which

A fir, 50 ins. diam., bears N. 20° 45' E., 77 lks. dist., mkd.
T19S R8W S28 BT.

A fir, 17 ins. diam., bears S. 14° W., 52 lks. dist. mkd.
T19S R8W S32 BT.

Land, mountainous.

Soil, rocky clay.

Timber, heavy fir, hemlock, cedar, alder, maple, chinquapin,
dogwood, and madrona.

Undergrowth, dense vine maple, hazel, salal, arrowwood, rhododendron,
huckleberry, salmonberry, bracken and Oregon grape.

From the cor. of secs. 27, 28, 33 and 34.

N. 87° 32' W., between secs. 28 and 33.

Over mountainous land; through heavy timber and dense undergrowth;
descend 54 ft. over S. slope.

9.70 A stream, 3 lks. wide, course S.

10.15 A stream, 5½ lks. wide, course S.; ascend over broken SE. slope.

15.70 A small draw, drains S.; ascend 86 ft. over SE. slope.

20.70 Top of spur, slopes SW.; descend 76 ft. over SW. slope.

23.10 Bottom of dry ravine, course S.; ascend 458 ft. over very steep
E. slope.

35.60 Top of spur, slopes S. 30° E.; thence over broken S. slope.

39.77 Point for the ¼ sec. cor. of secs. 28 and 33, as determined
from the original bearing trees:

A fir, 50 ins. diam., bears N. 26° E., 45 lks. dist., mkd.
¼ S. BT.

A fir, 40 ins. diam., bears S. 75° W., 28 lks. showing old
blaze facing E.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground,
with brass cap mkd.

¼	S 28

	S 33
	1952

*FD. OK 9/80
W. EIMSTAD
M 89-77*

N. 88° 59' W., beginning new measurement.

Ascend 54 ft. over broken S. slope.

6.30 Top of spur, slopes SW.; descend 593 ft. over steep NW. slope,
changing to W.