

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivision, T. 19 S., R. 8 W.

CHAINS

From the cor. of secs. 21, 22, 27 and 28.

N. 88° 38' W., between secs. 21 and 28.

Over mountainous land; through heavy timber and dense undergrowth; descend 393 ft. over SW. slope.

10.90 A stream, 4 lks. wide, course NW.; ascend 190 ft. over steep E. slope.

15.80 Top of spur, slopes NW.; descend 168 ft. over steep NW. slope.

20.15 A stream, 2 lks. wide, course N.; ascend 303 ft. over steep NE. slope.

25.60 Top of spur, slopes N.; descend 151 ft. on steep NW. slope.

30.00 Ravine, drains N. 10° E.; ascend 231 ft. over NE. slope.

35.10 Top of spur, slopes N.; descend 167 ft. over steep NW. slope.

38.71 Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28 as determined from the original bearing trees:A fir, 42 ins. diam., bears N. 79 $\frac{1}{2}$ ° W. 60 lks. dist., with an old blaze facing SE., with $\frac{1}{4}$ cut in bark.

A maple stump, 20 ins. diam., bears S. 45° W., 36 lks. dist., with a decayed blaze on NE. face.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

S 21

 $\frac{1}{4}$ ———

S 28

1952

from which

A fir, 35 ins. diam., bears N. 11° 45' E., 155 lks. dist., mkd. $\frac{1}{4}$ S21 BT.A cedar, 7 ins. diam., bears S. 9° E., 50 lks. dist., mkd. $\frac{1}{4}$ S28 BT.

N. 88° 43' W., beginning new measurement.

Ascend 45 ft. along very steep and broken N. slope.

7.50 A sidehill draw, drains N.

11.00 Top of high spur, slopes NW.; descend 573 ft. over steep, broken SW. slope.

35.30 Unimproved road, bears NW. and SE.

37.60 Esmond Creek, 24 lks. wide, course NW.; ascend 13 ft.

39.81 The corner of secs. 20, 21, 28 and 29.

Land, mountainous.

Soil, rocky clay.

Timber, heavy fir, hemlock, cedar, alder, maple, chinquapin, dogwood, and madrona.

Undergrowth, dense vine maple, hazel, arrowwood, salal and bracken.