

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivision, T. 19 S., R. 8 W.

CHAINS

A fir, 33 ins. diam., bears N. 81° E., 22 lks. dist., mkd. $\frac{1}{4}$ S16 BT.

A fir, 40 ins. diam., bears S. 42 $\frac{1}{2}$ ° W., 74 lks. dist., mkd. $\frac{1}{4}$ S21 BT.

N. 89° 32' W., beginning new measurement.

Over bottom land, nearly level course.

2.25 An unimproved road, bears NE. and SW.

3.32 Esmond Creek, 20 lks. wide, course NE.

10.20 Leave bottom land and ascend 432 ft. over steep SE. slope.

22.30 Top of spur, slopes N. 10° E.; descend 393 ft. over steep W. slope.

31.60 A stream, 1 lk. wide, course NE.; ascend 306 ft. over steep SE slope.

39.91 The cor. of secs. 16, 17, 20 and 21.

Land, mountainous, across the canyon of Esmond Creek.
Soil, rocky clay.

Timber, heavy fir, hemlock, cedar, maple, alder, chinquapin, dogwood and madrona.

Undergrowth, dense vine maple, hazel, manzanita, huckleberry, salmonberry, blackberry, salal and bracken.

N. 0° 08' W., between secs. 16 and 17.

Over mountainous land; through heavy timber and dense undergrowth; ascend 83 ft. over steep E. slope.

3.60 Top of spur, slopes NE.; descend 369 ft. over steep N. slope.

12.10 Ravine, course NE.; ascend 87 ft. over SW. slope.

17.85 A shallow dry draw, drains SW.; ascend 368 ft. over broken S. slope.

31.50 Top of spur, slopes E.; descend 385 ft. over steep NE. slope.


40.72 Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17 as determined from the original bearing trees:

A fir, 19 ins. diam., bears N. 37° E., 31 lks. dist., mkd. with an old blaze on SW. face.

A fir, 32 ins. diam., bears N. 73 $\frac{1}{2}$ ° W., 22 lks. dist. with old blaze on SE. face.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, with brass cap mkd.



from which