

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivision, T. 19 S., R. 8 W.

CHAINS

A fir, 36 ins. diam., bears N. $86\frac{1}{2}^{\circ}$ E., 94 lks. dist., mkd. $\frac{1}{4}$ S16 BT.

An alder, 10 ins. diam., bears S. 64° W., 40 lks. dist., mkd. $\frac{1}{4}$ S17 BT.

N. 0° 31' E., beginning new measurement.

Descend 224 ft. over steep N. slope.

4.86 Trail, bears E. and W.

6.04 Leopold Creek, 20 lks. wide, course E.; ascend 442 ft. over SW. slope.

16.50 A stream, 2 lks. wide, course SE.

29.30 Top of spur, slopes SW.; descend 243 ft. over broken N. slope.

38.70 A dry ravine, drains NW.; continue descent along a W. slope.

41.21 Point for the cor. of secs. 8, 9, 16 and 17 as determined from the original bearing trees.

A fir, 46 ins. diam., bears N. 61° E., 75 lks. dist., with old blaze on SW. face.

A fir, 60 ins. diam., bears S. $28\frac{1}{2}^{\circ}$ E., 117 lks. dist., showing old blaze facing NW. (Record bearing, S. 29° E.)

A fir, 48 ins. diam., bears S. 46° W., 25 lks. dist., with healed blaze on NE. face. (Record bearing, S. $45\frac{1}{2}^{\circ}$ W.)

A fir, 48 ins. diam., bears N. $52\frac{1}{2}^{\circ}$ W., 30 lks. dist., with blaze facing SE. (Record bearing, N. 51° W.)

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T19S	R8W
S 8	S 9
S 17	S16
1952	

*FD. 1/ST
D. BAKER
M 96-4*

from which

A fir, 10 ins. diam., bears N. 42° 45' E., 65 lks. dist., mkd. T19S R8W S 9 BT.

A fir, 16 ins. diam., bears S. 21° E., 32 lks. dist., mkd. T19S R8W S16 BT.

A fir, 10 ins. diam., bears S. 21° W., 55 lks. dist., mkd. T19S R8W S17 BT.

A fir, 11 ins. diam., bears N. 70° W., 60 lks. dist., mkd. T19S R8W S 8 BT.

Land, mountainous.

Soil, rocky clay.

Timber, heavy fir, hemlock, cedar, maple, dogwood, alder, chinquapin, yew and madrona.

Undergrowth, dense vine maple, hazel, salal, manzanita, rhododendron, bracken and Oregon grape.