

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivision, T. 19 S., R. 8 W.

CHAINS

From the cor. of secs. 9, 10, 15 and 16

N. 88° 40' W., between secs. 9 and 16.

Over mountainous land; through heavy timber and dense undergrowth; on nearly level course along N. slope.

0.80 Top of spur, slopes W. from S. 80° E.; descend 468 ft. over W. slope.

11.77 A fir, 63 ins. diam.

12.59 A fir, 67 ins. diam.

16.20 Enter nearly level bottom land, edge bears N. and S.

21.45 A spring branch, 1 lk. wide, course NW.; continue gradual descent.

22.40 Center of bladed earth logging road, bears NE. and SW.

23.60 Center of old road, bears N. 10° E. and S.

25.50 Esmond Creek, 30 lks. wide, course N. 25° E.

28.40 Leave bottom land and ascend 270 ft. over E. slope to ¼ sec. cor.

33.00 Thence over broken NE. slope, continue ascent.

39.36 Point for the ¼ sec. cor. of secs. 9 and 16 as determined from the original bearing trees:

A fir, 30 ins. diam., showing healed blaze facing S., bears N. 5° 45' W., 84 lks. dist.

A fir stump showing a partly decayed blaze, bears S. 31° 45' E., 74 lks. dist.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

S 9
¼ _____
S 16
1952

from which

A fir, 15 ins. diam., bears N. 68° 45' E., 31 lks. dist., mkd. ¼ S 9 BT.

A fir, 10 ins. diam., bears S. 46° W., 28 lks. dist., mkd. ¼ S16 BT.

N. 88° 55' W. beginning new measurement.

Ascend 83 ft. over NE. slope.

3.50 Top of spur, slopes NE.; descend 65 ft. over NW. slope.

8.77 A dry draw, drains NE.; ascend 222 ft. over steep E. slope.

13.50 Top of spur, slopes N. 35° E.; descend 141 ft. over NW. slope.

16.95 Bottom of dry ravine, course NE.; ascend 225 ft. over steep E. slope, changing to N. 70° E.