

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the East Boundary, T. 19 S., R. 8 W.,
Willamette Meridian, Oregon

CHAINS

(Restoration of the 1891 survey of Charles M. Collier)

The cor. of Tps. 19 and 20 S., R. 8 W., is monumented with a shattered sandstone, 16 x 12 x 12 ins., firmly set, with incomplete chisel marks, located at the intersection of original blazed lines; the original bearing trees have been consumed by fire.

At the corner point

Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in the ground with brass cap marked:

T 19 S		
R 8 W		
S 36		T 20 S
<hr/>		
S 1		R 7 W
T 20 S		S 6
1949		

from which new bearing trees

A fir, 10 ins. diam., bears N. 2 $\frac{1}{4}$ ° W., 30 lks. dist., marked T19S R8W S36 BT.

A fir, 8 ins. diam., bears S. 85° W., 24 lks. dist., marked T20S R8W S 1 BT.

N. 0° 17' E., along the E. bdy. of sec. 36.

Ascend 147 ft. over SW. slope, through heavy timber and dense undergrowth.

- 3.45 A spur, slopes SE.; ascend 33 ft. along broken E. slope.
- 7.30 The head of a ravine, course S. 50° E.; ascend 161 ft. over SW. slope.
- 13.35 A spur, slopes SE.; descend 73 ft. over NE. slope.
- 16.90 A branch, 2 lks. wide, course SE.; ascend 399 ft. over S. slope.
- 26.40 A spur, slopes SE.; ascend 5 ft. over broken SE. slope.
- 27.50 Top of ascent on E. slope; descend 14 ft. along E. slope.
- 28.80 A ridge, bears N. and S. 30° W.; descend 70 ft. along rolling ridgetop.
- 34.68 The closing corner of Tps. 19 and 20 S., R. 7 W., at saddle in ridge; ascend 30 ft. along ridgetop.
- 39.45 The $\frac{1}{4}$ sec. cor. of sec. 36 only, determined at the record bearing from the original SE. bearing tree and at the record bearing and distance from the original SW. bearing tree as follows:

A fir, 36 ins. diam., bears S. 45 $\frac{1}{4}$ ° E., 22 lks. dist., plainly blazed and healed, but center of tree gutted by fire. (Record distance 23 lks.)

A fir stump, badly burned and decayed, 36 ins. diam., bears S. 60° W., 26 lks. dist., with no marks remaining.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

$\frac{1}{4}$ S 36	
1949	

from which new bearing trees:

Norma... From... Under... Aff... 1948