

County Surveyor's Record, Douglas County, Oregon

12553

Dependent Resurvey of the E. Bdy., T. 19 S., R. 8 W.

CHAINS

35.76

Point for the $\frac{1}{4}$ sec. cor. of sec. 30 only, at midpoint on the W. bdy. of sec. 30.

41.04

Point for the cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

T 19 S		T 19 S
S 24		R 7 W
S 25		S 30
R 8 W		1949

from which

A fir, 8 ins. diam., bears S. 4° W., 90 lks. dist., marked T19S R8W S25 BT.

A madrona, 6 ins. diam., bears N. 26° W., 22 lks. dist., marked T19S R8W S24 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, maple, hemlock, chinquapin, and madrona.

Undergrowth, vine maple, arrowwood, hazel, salal, slickleaf, manzanita, red huckleberry, and bracken.

N. 0° 23' E., along the E. bdy. of sec. 24.

Ascend 115 ft. over SW. slope, through young timber and dense undergrowth.

5.20

A ridge, bears N. 70° W. and S. 70° E.; desc. 280 ft. over steep N. slope.

10.30

A ravine, course N. 75° E.; ascend 290 ft. over SE. slope.

18.10

Same ridge, bears NE. and SW.; descend 90 ft. over NW. slope, changing to broken W. slope.

23.60

A spur, slopes NW.; descend 188 ft. over N. slope.

27.40

The head of a ravine, course N. 80° W.; descend 2 ft. along broken W. slope.

29.35

A spur, slopes N. 30° W.; descend 78 ft. over N. slope.

31.00

The head of a ravine, course W.; ascend 50 ft. over SW. slope.

35.45

Point for the closing corner of secs. 19 and 30, T. 19 S., R. 7 W.; ascend 24 ft. over SW. slope.

37.90

A spur, slopes NW.; descend 83 ft. over NE. slope.

41.04

The $\frac{1}{4}$ sec. cor. of sec. 24 only, determined at the record bearing and distance from both original bearing trees as follows:

A fir, 32 ins. diam., bears S. 24 $\frac{1}{2}$ ° E., 19 lks. dist., with blaze cleanly healed.

A rotted fir stump, 12 ins. diam., bears N. 60° W., 43 lks. dist., with blaze decayed.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd:

$\frac{1}{4}$ S 24	
1949	