

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the E. Bdy., T.19 S., R. 8 W.

CHAINS	
5.90	A wire fence, bears E. and W.
7.20	County road, bears SE. and W. on curve.
22.80	A ravine, at forks from NE. and NW., course S. 30° W.; ascend 429 ft. over SW. slope, changing to S. slope.
35.26	Point for the closing corner of secs. 18 and 19, T. 19 S., R. 7 W.; ascend 121 ft. over S. slope.
38.50	A ridge, bears N. 70° E. and S. 70° W.; desc. 90 ft. over N. slope.
40.43	The $\frac{1}{4}$ sec. cor. of sec. 13 only, determined at the record bearing from the original NE. bearing tree and the record bearing and distance from the original NW. bearing tree as follows: A maple, 18 ins. diam., bears N. 43° E., 59 lks. dist., with blaze decayed. (Record distance 70 lks.) A fir, 46 ins. diam., bears N. 78 $\frac{1}{2}$ ° W., 24 lks. dist.; I partially open blaze and uncover the scribe marks BT at proper age. At the corner point Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked: <div style="text-align: center;"> $\frac{1}{4}$ S13 1949 </div> from which a new bearing tree A fir, 60 ins. diam., bears S. 40 $\frac{1}{4}$ ° W., 66 lks. dist., marked $\frac{1}{4}$ S13 BT. <hr style="width: 20%; margin: auto;"/> N. 0° 10' W., beginning new measurement. Descend 210 ft. over steep N. slope, through heavy timber and dense undergrowth.
3.55	A ravine, course N. 70° W.; ascend 145 ft. over SW. slope.
11.70	A spur ridge, bears NW. and SE.; descend 260 ft. over NE. slope.
17.60	A ravine, course NE.; descend 120 ft. along broken E. slope, changing to NE. slope.
23.20	The dry bed of a stream, 4 lks. wide, course N. 30° W.; ascend 80 ft. over SW. slope.
28.50	A spur, slopes NW.; descend 108 ft. over N. slope.
30.55	A ravine, course N. 70° W.; ascend 120 ft. over SW. slope.
34.45	A spur, slopes NW.; descend 221 ft. over N. slope.
35.76	Point for the $\frac{1}{4}$ sec. cor. of sec. 18 only, at midpoint on the W. bdy. of sec. 18.
39.75	North Creek, 10 lks. wide, course S. 60° W.; ascend 7 ft. across bottom.
40.71	The cor. of secs. 12 and 13, determined at the record bearing and distance from the original NW. bearing tree as follows: A fir, 90 ins. diam., bears N. 58 $\frac{1}{2}$ ° W., 20 lks. dist., with partial scribe marks visible on unhealed blaze. At the corner point