

10053
 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the E. Bdy., T. 19 S., R. 8 W.

CHAINS

Ascend 160 ft. over S. slope.

40.66 The $\frac{1}{4}$ sec. cor. of sec. 1 only, determined at the record distance from each of the original bearing trees as follows:

A fir, 30 ins. diam., bears S. $20\frac{1}{2}^\circ$ W., 32 lks. dist., plainly blazed and healed. (Record bearing S. 17° W.)

A fir, 32 ins. diam., bears S. $81\frac{1}{2}^\circ$ W., 38 lks. dist., plainly blazed and healed. (Record bearing S. 31° W.)

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

$\frac{1}{4}$ S 1
 1949

from which a new bearing tree

A fir, 11 ins. diam., bears N. $47\frac{1}{2}^\circ$ W., 37 lks. dist. mkd. $\frac{1}{4}$ S 1 BT.

N. $0^\circ 06'$ W., beginning new measurement.

Ascend 490 ft. over broken SW. slope.

23.05 A spur, slopes S. 20° E.; descend 20 ft. along broken E. slope.

25.10 A ravine, course S. 80° E.; ascend 55 ft. over SE. slope.

28.30 A spur, slopes E.; descend 358 ft. over N. slope.

30.00 Enter land slide area.

35.15 A wet ravine, course N. 80° E.; ascend 158 ft. over SE. slope.

35.20 Point for the $\frac{1}{4}$ sec. cor. of sec. 6 only, at proportionate distance on the W. bdy. of sec. 6.

40.95 A spur, slopes E.; descend 518 ft. over NE. slope; leave land slide area.

55.35 A branch, 8 lks. wide, course N. 80° E.; asc. 86 ft. over broken S. slope.

58.40 A spur, slopes N. 80° E.; descend 105 ft. over NE. slope.

66.20 Intersect the Fourth Standard Parallel South.

Point for closing cor. of Tps. 19 S., Rs. 7 and 8 W., determined at the record bearing and distance from the original SE. bearing tree as follows:

A sawed fir stump, 46 ins. diam., bears S. 52° E., 47 lks. dist., marked T19S R7W S 6 CC BT.

At the corner point

Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in the ground, with brass cap marked

T 18 S R 7 W
 S 31
 S 1/S 6
 R 8 W | R 7 W
 T 19 S
 C C
 1949