County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a portion of the E. Bdy., T. 23 S., R. 1 W.

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, & in a mound of stone, 2 ft. base to top, with brass cap mkd.

T 23 S | T 23 S
S 13 | R 1 E
S 24 | S 19
R 1 W
1960

from which

A fir, 6 ins. diam., bears S. 9½° W., 14 lks. dist., mkd. T23S R1W S24 BT.

Deposit original corner stone alongside iron post.

N. 0° 39' W., along E. bdy of sec. 13, marking and blazing true line.

Ascend 320 ft. over SW. slope, through heavy timber and dense undergrowth.

7.00 Spur, slopes SW.; desc. 135 ft. over NW. slope.

15.77 The original cor. of secs. 18 and 19, only, W. bdy. T. 23 S., R. 1 E., monumented with an iron post, 2 ins. diam., firmly set, 10 ins. above the ground, with brass cap mkd.

T 23 S | T 23 S
R 1 W | S 18
S 19
S 13 | R 1 E
1925

from which the original bearing trees

A pine, 25 ins. diam., bears N. 24½° E., 38 lks. dist., with healed blaze. (Record bearing N. 33° E.)

A pine, 16 ins. diam., bears S. 71° E., 76 lks. dist., with healed blaze. (Record, S. 74° E., 67 lks.)

N. 0° 25' E., beginning new measurement

Descend 300 ft. over NW. slope.

8.21 Creek, 2 lks. wide, course W.; asc. 105 ft. over SW. slope.

11.90 Spur, slopes W.; desc. 232 ft. over NW. slope.

16.25 Creek, 2 lks. wide, course W.; asc. 264 ft. over SW. slope.

22.46 The ¼ sec. cor. of sec. 13 only, monumented with an iron post, 1 in. diam., firmly set, 6 ins. above the ground, with brass cap mkd.

¼ S13
1925

from which the 1925 bearing trees

A fir, 8 ins. diam., bears S. 23° W., 9 lks. dist., with healed blaze.

A madrone stump, 10 ins. diam., bears N. 37° W., 45 lks. dist., with healed blaze.

and new bearing tree

+ +