

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the N. Bdy., T. 23 S., R. 1 W.

CHAINS

- 45.85 Top of ascent, slopes S.; desc. 59 ft. over SW. slope.
- 53.60 Creek, 2 lks. wide, course SE.; asc. 480 ft. over NE. slope.
- 77.98 Dirt access road, 15 lks. wide, bears N. and S.
- 78.20 The cor. of secs. 4, 5, 32, and 33, monumented with the original basalt stone, 12 x 10 x 6 ins., firmly set, 6 ins. above the ground mkd. with 4 notches on the E., and 2 notches on the W. edge, from which the original bearing trees:
- A fir, 18 ins. diam., bears N. $55\frac{1}{2}^{\circ}$ E., 42 lks. dist., with scribe marks 22S RLW BT, visible on partially opened blaze.
- A hemlock, 28 ins. diam., bears S. 20° E., 101 lks. dist., with scribe marks RLW S4 BT, visible on partially opened blaze.
- A hemlock, 16 ins. diam., bears S. 49° W., 75 lks. dist., with scribe marks 23 S RLW S5 BT, visible on partially opened blaze.
- A hemlock, 22 ins. diam., bears N. 58° W., 51 lks. dist., with scribe marks RLW S32 BT, visible on partially opened blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground and in a mound of stone, $1\frac{1}{2}$ ft. base to top, with brass cap mkd.

T 22 S R 1 W
 S 32 | S 33
 S 5 | S 4
 T 23 S
 1960

Deposit original corner stone alongside iron post.
 Land, mountainous
 Soil, rocky and clay loam.
 Timber, fir, hemlock, cedar, and madrona; undergrowth, reproduction, and vine maple.

Dependent Resurvey of a Portion of the Subdivisional Lines,
 T. 23 S., R. 1 W.
 (Restoring the 1893 Survey by Henry L. Chandler)

From the cor. of secs. 25, 26, 35, and 36, monumented with the original basalt stone, 12 x 10 x 5 ins., firmly set 6 ins. above the ground, marked with one notch on the S. and E. edge, from which the original bearing trees:

- A hemlock, 10 ins. diam., bears N. 20° E., 16 lks. dist., with ahealed blaze.
- A fir, 39 ins. diam., bears S. 50° E., 10 lks. dist., bark scribed T23S RLW S36 BT.
- A cedar, 18 ins. diam., bears S. 20° W., 13 lks. dist., with healed blaze.
- A fir, 39 ins. diam., bears N. 65° W., 36 lks. dist., with healed blaze. (Record distance, 39 lks.)

At the corner point