

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 23 S., R. 1 W.

CHAINS	
	<p>from which</p> <p>A fir, 53 ins. diam., bears N. 35° E., 51 lks. dist., mkd. W 1/16 S24 BT.</p> <p>A pine, 13 ins. diam., bears S. 53° W., 49 lks. dist., mkd. W 1/16 S25 BT.</p> <p>Ascend 363 ft. over SE. slope.</p>
75.30	Spur, slopes SE.; desc. 63 ft. over SW. slope.
80.38	The cor. of secs. 23, 24, 25, and 26.
	<p>Land, mountainous. Soil, rock and clay loam. Timber, fir, cedar, hemlock, and madrona. Undergrowth, vine maple, salal, and reproduction.</p>
	<p>N. 1° 31' E., bet. secs. 23 and 24.</p> <p>Ascend 406 ft. over SE. slope, through heavy timber and dense undergrowth.</p>
9.50	Ridge, bears NE. and SW., also Silica Trail on ridge top, bears the same; desc. 900 ft. over NW. slope.
36.455	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the orig. corner.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 25 ins. in the ground, and in a mound of stone, 1$\frac{1}{2}$ ft. base to top, with brass cap mkd.</p>
	<p>T 23 S R 1 W</p> <p> $\frac{1}{4}$</p> <p> S 23 S 24</p> <p> 1960</p>
	<p>from which</p> <p>A hemlock, 18 ins. diam., bears S. 84° E., 74 lks. dist., mkd. $\frac{1}{4}$ S24 BT.</p> <p>A maple, 15 ins. diam., bears S. 42° W., 69 lks. dist., mkd. $\frac{1}{4}$ S23 BT.</p> <p>Ascend 80 ft. over SW. slope.</p>
38.40	Spur, slopes W.; desc. 640 ft. over broken NW. slope.
72.91	<p>The cor. of secs. 13, 14, 23 and 24, monumented with the original basalt stone, 18 x 11 x 5 ins., firmly set, 10 ins. above the ground marked with 3 notches on the S. and 1 notch on the E. edge, from which the original bearing trees:</p> <p>A fir, 55 ins. diam., bears N. 25° E., 109 lks. dist., with scribe marks T23 RS visible on bark blaze. (Record distance, 115 lks.)</p> <p>A cedar, downed and rotted, 14 ins. diam., bears S. 40° E., 30 lks. dist., with healed blaze.</p> <p>A fir, 23 ins. diam., bears S. 48° W., 112 lks. dist., with scribe marks T23S R1W S23 BT visible on open blaze.</p> <p>A cedar, 10 ins. diam., bears N. 40° W., 26 lks. dist., with illegible scribe marks visible on partially opened blaze.</p>