County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 23 S., R. 1 W.

CHAINS	
	At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, 2 ft. base to top, with brass cap mkd. T 23 S R 1 W S 14 | S 13 S 23 | S 24 1960 From which A fir, 12 ins. diam., bears S. 35° E., 79 lks. dist., mkd. T23S R1W S24 BT. A hemlock, 10 ins. diam., bears S. 28° W., 27 lks. dist., mkd. T23S R1W S23 BT. Deposit original corner stone alongside iron post. Land, mountainous. Soil, rocky and clay loam. Timber, fir, cedar, hemlock and madrona. Undergrowth, vine maple, salal and reproduction.
	From the cor. of secs. 13 and 24, only, on the E. bdy. of the Tp. S. 84° 19' W., bet. secs. 13 and 24. Descend 409 ft. over SW. slope, through heavy timber and dense undergrowth.
12.75	Martin Creek road, gravelled, 25 lks. wide, bears SE. and NW. curving N.
14.80	Martin Creek, 30 lks. wide, course NW.; asc. 819 ft. over NE. slope.
39.81	Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, & in a mound of stone, 1½ ft. base to top, with brass cap mkd. T 23 S R 1 W ¼ S 13 S 24 1960 from which A hemlock, 18 ins. diam., bears N. 14½° E., 25 lks. dist., mkd. ¼ S13 BT. A hemlock, 6 ins. diam., bears S. 13° W., 11 lks. dist., mkd. ¼ S24 BT. Ascend 174 ft. over NE. slope.
43.79	Silica Trail, bears N. 20° W., and S. 20° E.
45.86	Ridge, bears N. 20° W., and S. 20° E.; desc. 565 ft. over W. slope.
54.15	Ravine, drains NW.; asc. 179 ft. over NE. slope.
66.20	Spur, slopes N.; desc. 255 ft. over NW. slope.
79.62	The cor. of secs. 13, 14, 23 and 24.

+ +