

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 23 S., R. 1 W.

CHAINS	<p>27.30 Sharps Creek, 30 lks. wide, course NW.; asc. 385 ft. over SW. slope.</p> <p>40.69 The cor. of secs. 1, 2, 35 and 36. on the N. bdy. of the Tp.</p> <p>Land, mountainous. Soil, rock and clay loam. Timber, fir, cedar, hemlock and madrona. Undergrowth, salal, vine maple and reproduction.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 88° 52' W., bet. secs. 26 and 35.</p> <p>Descend 368 ft. over NW. slope, through heavy timber and dense undergrowth.</p> <p>9.55 Creek, 10 lks. wide, course N.; asc. 620 ft. over NE. slope.</p> <p>38.20 Spur, slopes N.; desc. 21 ft. over NW. slope.</p> <p>40.33 The $\frac{1}{4}$ sec. cor. of secs. 26 and 35, monumented with the original basalt stone, 12 x 10 x 6 ins., firmly set, 4 ins. above the ground, mkd. $\frac{1}{4}$ on the N. face, from which the remaining original bearing tree:</p> <p style="padding-left: 40px;">A fir, 55 ins. diam., bears S. 65° E., 53 lks. dist., with healed blaze. (Record bearing, S. 75° E.)</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam, 24 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 S R 1 W</p> <p>$\frac{1}{4}$ S 26</p> <p>S 35</p> <p>1960</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 44$\frac{1}{2}$° E., 42 lks. dist., mkd. $\frac{1}{4}$ S26 BT.</p> <p style="padding-left: 40px;">Deposit original corner stone alongside iron post.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>S. 89° 13' W., beginning new measurement.</p> <p>Descend 105 ft. over NW. slope.</p> <p>5.27 Creek, 3 lks. wide, course NE.; asc. 1,191 ft. over E. slope.</p> <p>38.65 Dirt road, 20 lks. wide, bears NW. and SE.</p> <p>41.25 The corner of secs. 26, 27, 34 and 35, monumented with the original basalt stone, 16 x 12 x 6 ins., firmly set, 6 ins. above the ground, with 1 notch on the S., and 2 notches on the E. edge, from which the original bearing trees:</p> <p style="padding-left: 40px;">A hemlock, 19 ins. diam., bears N. 58$\frac{1}{2}$° E., 13 lks. dist., with healed blaze. (Record bearing, N. 50° E.)</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 20° E., 26 lks. dist., with scribe mks. 23S 35 visible on opened blaze.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 9$\frac{1}{4}$° W., 22 lks. dist., with illegibel scribe mks. visible on opened blaze. (Record bearing and distance, S. 6° W., 25 lks.)</p>
--------	---