

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 23 S., R. 1 W.

CHAINS

A sugar pine, 22 ins. diam., bears N.  $70\frac{1}{2}^\circ$  W., 11 lks. dist., with scribe mks. T2 R visible on partially opened blaze. (Record bearing, N.  $85^\circ$  W.)

At the corner point.

Set an ironpost, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground & in a mound of stone,  $2\frac{1}{2}$  ft. base to top, with brass cap mkd.

T 23	S R 1	W
S 27		S 26
S 34		S 35
1960		

from which

A fir, 10 ins. diam., bears S.  $37^\circ$  E., 51 lks. dist., mkd. T23S R1W S35 BT.

A fir, 10 ins. diam., bears S.  $28^\circ$  W., 23 lks. dist., mkd. T23S R1W S34 BT.

Deposit original corner stone alongside iron post.

Land, mountainous.

Soil, rocky and clay loam.

Timber, fir, cedar, and hemlock; Undergrowth, salal, vine maple, and reproduction.

N.  $5^\circ 13'$  E., bet. secs. 26 and 27.

Descend 650 ft. over NE. slope, through heavy timber and dense undergrowth.

- 1.07 Silica Trail, bears E. and W.
- 3.63 Dirt road, 20 lks. wide, bears NW. and SE.
- 26.80 Creek, 2 lks. wide, course NE.; asc. 21 ft. over SE. slope.
- 28.80 Spur, slopes E.; desc. 37 ft. over NE. slope.
- 31.20 Ravine, drains E.; asc. 44 ft. over SE. slope.
- 33.25 Spur, slopes NE.; desc. 60 ft. over NE. slope.
- 36.00 Ravine, drains. E.; asc. 20 ft. over SE. slope.
- 36.57 The  $\frac{1}{4}$  sec. cor. of secs. 26 and 27, determined at record bearing and distance from the original bearing trees:

A fir, 9 ins. diam., bears S.  $87^\circ$  E., 8 lks. dist., with a healed blaze.

A hemlock, 22 ins. diam., bears S.  $57^\circ$  W., 18 lks. dist., with a healed blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 25 ins. in the ground and in a mound of stone, 2 ft. base to top, with brass cap mkd.

T 23	S R 1	W
$\frac{1}{4}$		
S 27/S 26		
1960		