

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 23 S., R. 1 W.

CHAINS					
	<p>A fir, 8 ins. diam., bears S. 72° E., 32 lks. dist., mkd. $\frac{1}{4}$ S23 BT.</p> <p>A fir, 13 ins. diam., bears N. 71$\frac{1}{2}$° W., 22 lks. dist., mkd. $\frac{1}{4}$ S22 BT.</p> <p>Descend 354 ft. over NE. slope.</p>				
52.25	Creek, 3 lks. wide, course NE.; asc. 34 ft. along E. slope.				
55.25	Top of ascent, slopes E., desc. 149 ft. over NE. slope.				
57.60	Dry creek bottom, 8 lks. wide, course SE.; asc. 390 ft. over SE. slope.				
72.75	Top of ascent, slopes E.; desc. 199 ft. over NE. slope.				
79.97	<p>The corner of secs. 14, 15, 22 and 23, determined at record bearing and distance from the original bearing trees:</p> <p>A fir, 42 ins. diam., bears N. 87° E., 37 lks. dist., with bark scribed T23S RLW 14 visible.</p> <p>A fir, 16 ins. diam., bears S. 72° E., 54 lks. dist., with healed blaze.</p> <p>A fir, 24 ins. diam., bears S. 76° W., 18 lks. dist., with healed blaze.</p> <p>A fir snag, 8 ins. diam., bears N. 69$\frac{1}{2}$° W., 17 lks. dist., with healed blaze.</p> <p>At the corner Point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 18 ins. in the ground, to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 S R 1 W</p> <table border="1" style="margin: auto;"> <tr> <td>S 15</td> <td>S 14</td> </tr> <tr> <td>S 22</td> <td>S 23</td> </tr> </table> <p>1960</p> </div> <p>from which</p> <p>A fir, 18 ins. diam., bears N. 38$\frac{1}{2}$° W., 35 lks. dist., mkd. T23S RLW S15 BT.</p> <p>Land, mountainous. Soil, ricky and clay loam. Timber, fir, cedar, hemlock, and madrona. Undergrowth, vine maple, salal and reproduction.</p>	S 15	S 14	S 22	S 23
S 15	S 14				
S 22	S 23				
	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 86° 58' W., bet. secs. 14 and 23.</p> <p>Descend 258 ft. over NW. slope, through heavy timber and dense undergrowth.</p>				
6.11	Clark Creek, 15 lks. wide, course N.; asc. 102 ft. over SE. slope.				
7.35	Clark Creek road, gravelled, 40 lks. wide, bears NE. and SW.				
12.50	Spur, slopes SE.; desc. 38 ft. over SW. slope.				
18.45	Creek, 10 lks. wide, course SE.; asc. 120 ft. along broken N. slope.				
37.80	Creek, 10 lks. wide, course NE.; asc. 60 ft. along N. slope.				