

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 23 S., R. 1 W.

CHAINS

Ascend 36 ft. over NE. slope, through scattering timber and dense undergrowth.

2.25 Silica Trail and spur ridge, bears S. and N., curving E.; desc. 1,200 ft. over NW. slope.

35.80 Creek, 1 lk. wide, course NW.

35.90 The $\frac{1}{4}$ cor. of secs. 27 and 34, determined at record distance from the original bearing trees:

A fir, 22 ins. diam., bears N. 50° E., 47 lks. dist., with healed blaze. (Record bearing, N. 40° E.)

A fir, 26 ins. diam., bears S. 3° W., 38 lks. dist., with healed blaze. (Record bearing, S. 18° W.)

At the corner point

Set an iron post, 28 ins. long. $2\frac{1}{2}$ ins. diam., on bedrock, and in a mound of stone, 5 ft. base to top, with brass cap mkd.

T 23 S R 1 W
 $\frac{1}{4}$ $\frac{S 27}{S 34}$
1960

S. 89° 35' W., beginning new measurement.

Ascend 245 ft. over NE. slope.

8.15 Spur, slopes NW.; desc. 711 ft. along N. slope.

38.34 The cor. of secs. 27, 28, 33, and 34, determined at record distance from the remaining original bearing trees:

A hemlock, 23 ins. diam., bears N. 88° E., 45 lks. dist., with healed blaze.

A cedar, 35 ins. diam., bears S. 60° W., 33 lks. dist., with scribe marks TS RLW visible on partially opened blaze. (Record bearing, S. 80° W.)

A fir, 65 ins. diam., bears N. 58° W., 58 lks. dist., with bark scribe mark T visible.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 25 ins. in the ground, and in a mound of stone, 2 ft. base to top, with brass cap mkd.

T 23 S R 1 W
 $\frac{S 28}{S 33} | \frac{S 27}{S 34}$
1960

from which

A hemlock, 9 ins. diam., bears S. 26° E., 37 lks. dist., mkd. T23S RLW S34 BT.

A hemlock, 6 ins. diam., bears S. 43° W., 41 lks. dist., mkd. T23S RLW S33 BT.

Land, mountainous.

Soil, rocky and clay loam.

Timber, fir, cedar, hemlock and madrona.

Undergrowth, vine maple, salal, and reproduction.