

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 23 S., R. 1 W.

CHAINS 36.50	<p>The Cor. of secs. 21, 22, 27, and 28, monumented with the original basalt stone, 14 x 14 x 8 ins., firmly set, 6 ins. above the ground, marked with 3 notches on the E. edge, and other illegible marks on the S. edge, from which the remains of the original bearing trees:</p> <p>A rotted fir stump, 25 ins. diam., bears N. 17° E., 60 lks. dist.</p> <p>A rotted fir stump, 22 ins. diam., bears S. 30° E., 148 lks. dist., with scribe marks T23S RLW S27 BT visible on partially opened blaze.</p> <p>A fir snag, 45 ins. diam., bears N. 62° W., 162 lks. dist., with scribe marks T S21 visible on partially opened blaze. (Record distance, 189 lks.)</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, & in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T 23 S R 1 W</td></tr> <tr><td>S 21 S 22</td></tr> <tr><td>S 28 S 27</td></tr> <tr><td>1960</td></tr> </table> </div> <p>from which</p> <p>A pine, 16 ins. diam., bears N. 66° E., 10 lks. dist., mkd. T23S RLW S22 BT.</p> <p>A fir, 8 ins. diam., bears S. 57° E., 9 lks. dist., mkd. T23S RLW S27 BT.</p> <p>A fir, 13 ins. diam., bears S. 52° W., 26 lks. dist., mkd. T23S RLW S28 BT</p> <p>A fir, 10 ins. diam., bears N. 41° W., 48 lks. dist., mkd. T23S RLW S21 BT</p> <p>Deposit original corner stone alongside iron post</p> <p>Land, mountainous. Soil, rocky and clay loam. Timber, fir, cedar, hemlock and madrona. Undergrowth, salal, vine maple, and reproduction.</p>	T 23 S R 1 W	S 21 S 22	S 28 S 27	1960
T 23 S R 1 W					
S 21 S 22					
S 28 S 27					
1960					
4.40 9.20 13.20 16.00 18.50 24.50 35.75 38.30	<p>From the corner of secs. 22, 23, 26 and 27.</p> <p>N. 89° 32' W., bet. secs. 22 and 27.</p> <p>Ascend 111 ft. over NE. slope, through heavy timber and dense undergrowth.</p> <p>Spur, slopes N.; desc. 121 ft. over NW. slope.</p> <p>Ravine, drains N.; asc. 88 ft. over NE. slope.</p> <p>Spur, slopes N.; desc. 67 ft. over NW. slope.</p> <p>Ravine, drains N.; asc. 87 ft. over NE. slope.</p> <p>Spur, slopes N.; desc. 100 ft. over NW. slope.</p> <p>Creek, 10 lks. wide, course NE.; asc. 465 ft. over NE. slope.</p> <p>Spur, slopes N.; desc. 46 ft. over NW. slope.</p> <p>The ¼ sec. cor. of secs. 22 and 27, determined at record bearing and distance from the original bearing trees:</p>				