

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 23 S., R. 1 W.

CHAINS

A fir, 42 ins. diam., bears N. 50° W., 23 lks. dist.,
with healed blaze.

A hemlock, 35 ins. diam., bears S. 85° W., 36 lks. dist.,
with healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground,
and in a mound of stone, 2 ft. base to top, with brass cap mkd.

T 23 S R 1 W
 $\frac{1}{4}$ S 22
S 27
1960

N. 89° 25' W., beginning new measurement.

Ascend 595 ft. over NE. slope.

24.50 Ridge, bears NW. and SE.; desc. 337 ft. over SW. slope.

26.00 Dirt road, 20 lks. wide, bears NW. and SE.

38.69 The cor. of secs. 21, 22, 27 and 28.

Land, mountainous.

Soil, rocky and clay loam.

Timber, fir, cedar, hemlock, and madrone.

Undergrowth, salal, vine maple, and reproduction.

N. 2° 45' W., bet. secs. 21 and 22.

Ascend 600 ft. over SW. slope, through heavy timber and dense
undergrowth.

15.50 Dirt road, 20 lks. wide, bears NW. and E.

16.50 Ridge, bears E. and W.; desc. 435 ft. over NE. slope.

28.50 Clark Creek, 10 lks. wide, course E.; asc. 305 ft. over SE. slope.

39.645 Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22, at proportionate
distance; there is no remaining evidence of the orig. corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground,
and in a mound of stone, 2 ft. base to top, with brass cap mkd.

T 23 S R 1 W
S 21 | $\frac{1}{4}$ S 22
1960

from which

A fir, 8 ins. diam., bears N. $46\frac{1}{2}$ ° E., 26 lks. dist.,
mkd. $\frac{1}{4}$ S22 BT.

A fir, 10 ins. diam., bears S. 80° W., 26 lks. dist.,
mkd. $\frac{1}{4}$ S21 BT.

Ascend 360 ft. over SE. slope.

66.40 Ridge, bears E. and W.; desc. 530 ft. over NE. slope.