

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 23 S., R. 1 W.

CHAINS

79.29

The cor. of secs. 15, 16, 21 and 22, monumented with the original basalt stone, 12 x 10 x 6 ins., firmly set, 6 ins. above the ground, from which the original bearing trees:

A fir snag, 33 ins. diam., bears N. 52° E., 46 lks. dist., with illegible scribe marks visible on bark blaze.

A hemlock, 15 ins. diam., bears S. 28½° E., 42 lks. dist., with illegible scribe marks visible on partially opened blaze.

A hemlock, 13 ins. diam., bears S. 57½° W., 29 lks. dist., with scribe marks 3 21 visible on partially opened blaze.

A hemlock, 15 ins. diam., bears N. 27° W., 33 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, & in a mound of stone, 2 ft. base to top, with brass cap mkd.

T 23 S R 1 W			
S 16		S 15	
S 21		S 22	
1960			

from which

A fir, 7 ins. diam., bears N. 74° E., 11 lks. dist., mkd. T23S RLW S15 BT.

Deposit corner stone alongside corner iron post.

Land, mountainous.  
Soil, rocky and clay loam.  
Timber, fir, cedar, hemlock, and madrona.  
Undergrowth, salal, vine maple and reproduction.

From the corner of secs. 14, 15, 22 and 23.

S. 89° 57' W., bet. secs. 15 and 22.

Ascend 757 ft. over NE. slope, through heavy timber and dense undergrowth.

22.80

Ridge, bears N. and S.; desc. 340 ft. over NW. slope.

32.30

Creek, 3 lks. wide, course N.; asc. 125 ft. over NE. slope.

38.69

The ¼ sec. cor. of secs. 15 and 22, monumented with the original basalt stone, 18 x 14 x 8 ins., firmly set, 10 ins. above the ground, with illegible chisel marks on N. face, from which the original bearing trees:

A fir, 40 ins. diam., bears N. 7° E., 17 lks. dist., with illegible bark scribe marks visible.

A fir, 30 ins. diam., bears S. 68° E., 76 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 2 ft. base to top, with brass cap mkd.

T 23 S R 1 W			
¼		S 15	
		S 22	
1960			