

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 23 S., R. 1 W.

CHAINS

Deposit corner stone alongside iron post

N. $89^{\circ} 49'$ W., beginning new measurement.

Ascend 335 ft. over NE. slope.

13.40 Spur, slopes NE.; desc. 370 ft. over NW. slope.

27.85 Creek, 5 lks. wide, course N. ; asc. 30 ft. over broken NE. slope.

38.21 The corner of secs. 15, 16, 21 and 22.

Land, mountainous.

Soil, rocky and clay loam.

Timber, fir, cedar, hemlock, and madrona.

Undergrowth, salal, vine maple and reproduction.

From the cor. of secs. 20, 21, 28 and 29, monumented with the original basalt stone, 24 x 18 x 12 ins., firmly set, 10 ins. above the ground, marked with 4 notches on the E. and 2 notches on the S. edge, from which the original bearing trees:

A fir, 30 ins. diam., bears N. $63\frac{1}{2}^{\circ}$ E., 40 lks. dist., with a healed blaze.

A fir, 26 ins. diam., bears S. 86° E., 35 lks. dist., with a healed blaze.

A fir, 25 ins. diam., bears S. 45° W., 17 lks. dist., mkd. with a healed blaze.

A fir, 22 ins. diam., bears N. 31° W., 14 lks. dist., mkd. with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, & in a mound of stone, 3 ft. base to top, with brass cap mkd.

T 23 S R 1 W
S 20 S 21
S 29 S 28
1960

Deposit original corner stone alongside iron post.

N. $0^{\circ} 27'$ E., bet. secs. 20 and 21.

Ascend 415 ft. over SE. slope, through heavy timber and dense undergrowth.

18.50 Ridge, bears NE. and SW.; desc. 490 ft. over NW. slope.

38.74 The $\frac{1}{4}$ sec. cor. of secs. 20 and 21, monumented with the original basalt stone, 16 x 12 x 10 ins., firmly set, 10 ins. above the ground, with $\frac{1}{4}$ marked on W. face, from which the remaining original bearing tree:

A fir snag, 7 ins. diam., bears N. 42° E., 9 lks. dist., with $\frac{1}{4}$ S visible on partially opened blaze. (Record bearing N. 70° E.)

and locally established bearing tree

A fir, 22 ins. diam., bears N. 59° W., 27 lks. dist., with illegible scribe marks visible on partially opened blaze.