

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 23 S. R. 1 W.

CHAINS

A fir, 15 ins. diam., bears S. 60° E., 33 lks. dist.,
mkd. T23S RLW S21 BT.

A fir, 10 ins. diam., bears S. 38° W., 48 lks. dist.,
mkd. T23S RLW S20 BT.

A fir, 13 ins. diam., bears N. 84° W., 16 lks. dist.,
mkd. T23S RLW S17 BT.

Deposit original corner stone alongside iron post.

Land, mountainous.

Soil, rocky and clay loam.

Timber, fir, cedar, hemlock, and madrona.

Undergrowth, salal, vine maple and reproduction.

Remonumentation of Certain Original Corner Points, T. 23 S., R. 1 W.

The following is the remonumentation of certain original corner points, T. 23 S., R. 1 W., as provided for in the General Special Instructions, Group No. 350, Oregon, dated May 3, 1957, "Investigation of Collateral of Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points With New Accessories When Needed".

(Remonumenting the corners established by Henry L. Chandler in 1893)

The original cor. of secs. 13, 18, 19 and 24, on the W. bdy of T. 23 S., R. 1 W., perpetuated with an iron pipe 2 ins. diam., firmly set, 24 ins. above the ground, at record bearing and distance from the original bearing trees:

A hemlock, 24 ins. diam., bears N. 38° E., 68 lks. dist.,
with scribe marks T23 R S visible on partially opened blaze.

A hemlock, 22 ins. diam., bears S. 61° E., 22 lks. dist.,
with healed blaze.

A fir snag, 50 ins. diam., bears S. 20° W., 32 lks. dist.,
with healed blaze.

A downed firm 60 ins. diam., bears N. 38° W., 39 lks. dist.,
with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, and in a mound of stone, 2 ft. base to top, with brass cap mkd.

T 23 S	
R 2 W	R 1 W
S 13	S 18
S 24	S 19
1960	

from which

A cedar, 30 ins. diam., bears S. 73½° W., 43 lks. dist.,
mkd. T23S R2W S24 BT.

A hemlock, 10 ins. diam., bears N. 10° W., 75 lks. dist.,
mkd. T23S R2W S13 BT.

Reset local corner marker alongside iron post.