

## County Surveyor's Record, Douglas County, Oregon

Remonumentation of Certain Original Corner Points, T. 23 S., R. 1 W.

## CHAINS

The original cor. of secs. 1, 6, 7, and 12, on the W. bdy of T. 23 S., R. 1 W., determined at record bearing and distance from the remaining original bearing trees:

A maple, 12 ins. diam., bears N. 4° E., 38 lks. dist., with scribe marks W S6 visible on partially opned blaze.

A fir, 30 ins. diam., bears S. 64° E., 23 lks. dist., with healed blaze.

A fir, 38 ins. diam., bears S. 11° W., 62 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T 23 S
R 2 S   R 1 W
S 1   S 6
S 12   S 7
1960

from which

A fir, 6 ins. diam., bears N. 42° E., 53 lks. dist., mkd. T23S R1W S6 BT.

A fir, 8 ins. diam., bears N. 43° W., 31 lks. dist., mkd. T23S R2W S1 BT.

The original ¼ sec. cor. of secs. 16 and 21, determined at record bearing and distance from the remaining original bearing trees:

A fir, 40 ins. diam., bears N. 76° W., 34 lks. dist., with bark scribe marks ¼ visible.

A fir, 15 ins. diam., bears S. 2° E., 19 lks. dist., with scribe marks ¼ S visible on partially opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, & in a mound of stone, 3 ft. base to top, with brass cap mkd.

T 23 S R 1 W
¼ S 16
¼ S 21
1960

from which

A hemlock, 12 ins. diam., bears N. 39° E., 52 lks. dist., mkd. ¼ S16 BT.

A fir, 12 ins. diam., bears S. 27° W., 43 lks. dist., mkd. ¼ S21 BT.

## GENERAL DESCRIPTION

The lines resurveyed are located about eight miles southeast of Culp Creek, Oregon. Elevation ranges from 1,500 feet to 4,000 feet above sea level. The soil is a rocky clay loam covered with timber consisting of fir, cedar, hemlock, pine, and madrona. This