

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines, T. 21 S., R. 4 W.

CHAINS

40.03

Point for the cor. of secs. 25, 26, 35, and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 21 S	R 4 W
S 26	S 25
S 35	S 36
1958	

from which

A fir, 8 ins. diam., bears N. 32° E., 48 lks. dist., mkd.
T21S R4W S25 BT.

A fir, 14 ins. diam., bears S. 55° E., 47 lks. dist., mkd.
T21S R4W S36 BT.

A fir, 10 ins. diam., bears S. $48\frac{1}{4}^\circ$ W., 19 lks. dist., mkd.
T21S R4W S35 BT.

A fir, 9 ins. diam., bears N. $16\frac{3}{4}^\circ$ W., 39 lks. dist. mkd.
T21S R4W S26 BT.

From this point a locally established cor., bears S. 35° W., $34\frac{1}{2}$ lks. dist., monumented with a fir stake, 2 ins. sq., protruding 4 ft. above ground, firmly set, from which

A fir, 7 ins. diam., bears S. $72\frac{1}{2}^\circ$ E., 25 lks. dist. mkd.
S26 BT.

A fir, 7 ins. diam., bears S. $8\frac{3}{4}^\circ$ E., 45 lks. dist., mkd.
S36 BT.

A fir, 10 ins. diam., bears S. $26\frac{1}{2}^\circ$ W., 22 lks. dist., mkd.
S35 BT.

A fir, 10 ins. diam., bears N. 65° W., 10 lks. dist., mkd.
S26 BT.

Land, mountainous.

Soil, clay with rocky patches.

Timber, fir, cedar, hemlock, maple, and chinquapin.

Undergrowth, reproduction and salal.

From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the township, monumented with an iron pipe, 24 ins. long, $\frac{3}{4}$ in. diam., protruding 6 ins. above ground, firmly set; point falls by a fence bearing N. and S., from which the remains of the original bearing trees marked by James E. Freeman in 1851:

A rotted fir stump, 17 ins. diam., bears S. 73° E., 16 lks., dist., with scribe marks R3W T S 1 T visible on burned and chopped out blaze. (Record distance 15 lks.)

A burned fir snag, 38 ins. diam., bears S. 87° W., 118 lks. dist., with scribe marks R4W T21S S36 visible on partly opened blaze. (Record distance 18 lks.)

A fir, 30 ins. diam., bears N. 63° W., 23 lks. dist., with no scribe marks visible on burned out blaze. (Record dist. 20 lks.)

At the corner point.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.