

12389 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines, T. 21 S., R. 4 W.

CHAINS	Ascend 18 ft. over SE. slope.
42.30	Leave swamp, edge bears NW. and SE.; ascend 86 ft. over E. slope.
47.90	Ridge, bears NE. and W.; descend 26 ft. over W. slope.
57.20	Dirt access road, 15 lks. wide, bears NW. and SE.
57.00	Saddle in ridge, bears E. and W.; ascend 50 ft. over E. slope.
64.12	Dirt access road, 20 lks. wide, bears N. 80° E. and S. 80° W.
67.35	Leave ridge, bears E. and SW.; descend 92 ft. over NW. slope, through dense reproduction.
73.73	Spring branch, 1 lk. wide, course N.; ascend 9 ft. over NE. slope.
74.47	Spur, slopes N.; descend 64 ft. over NW. slope changing to N. slope.
80.41	The corner of secs. 25, 26, 35, and 36.
	Land, mountainous. Soil, clay and loam. Timber, fir, cedar, hemlock, chinquapin, alder, and maple. Undergrowth, reproduction and salal.
	N. 0° 29' W., between secs. 25 and 26.
	Descend 48 ft. over N. slope, through heavy 2nd growth timber and reproduction.
4.70	Creek, 3 lks. wide, course N. 30° E.; ascend 28 ft. over SE. slope.
10.30	Top of bluff, 90 ft. high, edge bears NE. and SW.
11.74	Foot of bluff, edge bears the same; descend 104 ft. over N. slope, changing to NE. slope.
16.33	Spring seepage, course N.; descend 48 ft. over N. slope.
18.83	Center of small swamp, 60 lks. wide, drains E.; descend 3 ft. over NE. slope.
20.015	Point for the S 1/16 cor. of secs. 25 and 26.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	S 1/16 S 26 S 25 1958
	from which
	A fir, 50 ins. diam., bears S.41°E., 43 lks. dist., mkd. S 1/16 S25 BT.
	A fir, 13 ins. diam., bears N. 42° W., 31½ lks. dist., mkd. S 1/16 S26 BT.
	Descend 5 ft. over NE. slope.
20.53	Spring branch, 1lk. wide, course N. 20° E.; descend 115 ft. over NE. slope.
25.26	Creek, 5 lks. wide, course N. 20° W.; ascend 28 ft. along W. slope.