

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines, T.21 S., R. 4 W.

CHAINS	
34.30	Spur ridge, bears N. 30° W. and S. 30° E.; descend 77 ft. over W. slope changing to SW. slope.
40.365	Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins in the ground, with brass cap mkd.
	<p style="text-align: center;">T 21 S R 4 W $\frac{1}{4}$ $\frac{S 26}{S 35}$ 1958 <i>FD OK PER PEEL MAY-87 M104-28</i></p>
	from which
	A fir, 10 ins. diam., bears N. $1\frac{1}{2}$ ° E., 61 lks. dist., mkd. $\frac{1}{4}$ S26 BT.
	A fir, 17 ins. diam., bears S. $57\frac{1}{4}$ ° E., 379 lks. dist., mkd. $\frac{1}{4}$ S35 BT.
	From this point a locally established cor., bears N. 17° 07' E., 35 lks. dist., monumented with an iron pipe, $1\frac{1}{4}$ ins. diam., protruding 4 ft. above ground, firmly set, from which
	A cedar, 15 ins. diam., bears N. 52° E., $53\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S 276 BT.
	A cedar, 27 ins. diam., bears S. 81° W., $166\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S 276 BT.
	Descend 81 ft. along S. slope, through heavy timber and light undergrowth.
49.62	Spur, slopes SW.; descend 44 ft. along S. slope.
51.05	Head of ravine, drains SW.; descend 11 ft. along S. slope.
54.08	Spur, slopes SW.; descend 34 ft. over W. slope.
56.50	Branch, 2 lks. wide, course S.; ascend 84 ft. along S. slope.
57.00	Top of ascent, slopes S.; descend 168 ft. along S. slope.
79.78	Spur, slopes S. 75° W.; descend 47 ft. over E. slope, along S. edge of logged area.
80.73	The cor. of secs. 26, 27, 34, and 35, monumented with a fir stake, 1 in. sq., 2 ft. long, protruding 18 ins. above ground, firmly set, point for cor. falls on a spur, sloping W.
	from which the remaining original bearing trees:
	A sawed fir stump, 38 ins. diam., bears N. 86° E., 39 lks. dist., with no marks visible. (Record distance 36 lks.)
	A fir, 50 ins. diam., bears S. 80° E., 39 lks. dist., bark scribed T21S R4W S35 over original bark scribes. (Record S. $8\frac{1}{2}$ ° E., 36 lks.)
	A fir, 38 ins. diam., bears S. 63° W., 20 lks. dist., bark scribed T21S R4W over illegible original bark scribes. (Record S. 68° W. 18 lks. dist.)
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.