

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 23 S., R. 3 W.

CHAINS

A sawed fir stump, 48 ins. diam., bears N. 43° E., 30 lks. dist., no marks remaining. (Record bearing, N. 10° E.)

and local bearing trees

A fir, 34 ins. diam., bears N. 23½° E., 209 lks. dist., with scribe marks S16 BT visible on a bark blaze.

A fir, 16 ins. diam., bears S. 12½° E., 136 lks. dist., with scribe mark S. visible on a bark blaze and healed blaze at base of tree.

A fir, 40 ins. diam., bears S. 3½° W., 121 lks. dist., with scribe marks S20 BT visible on a bark blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 23 S R 3 W
S 17 S16
S 20 S 21
1959

from which

A maple, 22 ins. diam., bears N. 9° W., 258 lks. dist., mkd. T23S R3W S17 BT.

Deposit stone alongside Iron Post.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, maple, alder, yew, dogwood and madrone. Undergrowth, vine maple, salal, Oregon grape, hazel, huckleberry, blackberry and poison oak.

N. 0° 46' E., bet. Secs. 15 and 16.

Descend 22 ft. over NE. slope, along E. edge of logged area, through scattered timber and dense undergrowth.

- 1.25 Branch, 1 lk. wide, course SE.; asc. 536 ft. over SE. slope changing to S. slope.
- 20.10 Gravel surface access road, 25 lks. wide, bears NE. and S. 30° W.
- 25.42 Spur ridge, bears NE. and S. 30° W.; desc. 145 ft. over NE. slope.
- 30.22 Dirt access road, 20 lks. wide, bears E. and W.
- 36.67 Gravel surfaced access road, 20 lks. wide, bears N. 20° W. and SE.
- 36.80 Leave timber, enter logged area, edge bears E. and S.
- 38.46 The ½ sec. cor. of secs. 15 and 16, perpetuated and recorded by M. D. Hale, Registered Surveyor, 1959, at record bearing and distance from the remains of the original SE. bearing tree, which is no longer in existence, monumented with an iron pipe, ½ in. diam., firmly set, 6 ins. above ground.

from which

A sawed cedar stump, 60 ins. diam., bears N. 69° E., 56 lks. dist., mkd. with a nail stamped "W" on the head.