

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the E. Bdy., T. 23 S., R. 3 W.

CHAINS

A hemlock snag, 10 ins. diam., bears N. $86\frac{3}{4}^{\circ}$ E., 65 lks. dist., with scribe marks S30 BT visible on a partially healed blaze facing the corner. (Record bearing, S. 45° E., record distance, 50 lks.) Chandler reported destroying the marks on this tree in his 1893 resurvey.

A fir, 67 ins. diam., bears N. 40° W., 15 lks. dist., with fragmentary scribe marks visible on bark blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T 23 S	
R 3 W	T 23 S
S 24	R 2 W
S 25	S 30
	1959

from which

A hemlock, 15 ins. diam., bears S. $46\frac{3}{4}^{\circ}$ W., $67\frac{1}{2}$ lks. dist., mkd. T23S R3W S25 BT.

A fir, 50 ins. diam., bears N. 23° W., 57 lks. dist., mkd. T23S R3W S24 BT.

N. $1^{\circ} 16'$ W., along the E. bdy. of sec. 24, marking and blazing the true line.

Descend 74 ft. over steep N. slope, through heavy timber and scattered undergrowth.

0.88 Creek, 3 lks. wide, course NE.; asc. 12 ft. over SE. slope.

1.95 Top of ascent, slopes E.; desc. 192 ft. over NE. slope.

9.04 The closing cor. of secs. 19 and 30, W. bdy. T. 23 S., R. 2 W., set by Chandler in 1893, determined at record distance from the remains of the original bearing trees. This now becomes a corner of minimum control for secs. 19 and 30.

from which

A cedar snag, 24 ins. diam., bears N. 56° E., 40 lks. dist., with scribe marks T23S R2W S19 visible on an open blaze.

A cedar, 30 ins. diam., bears S. 60° E., 53 lks. dist., with scribe marks T23S R2W S30 BT visible on a partially healed blaze. (Record bearing, S. 77° E.)

A cedar, 15 ins. diam., bears S. 44° W., 5 lks. dist., with scribe marks CC T23S R2W S19 S30 BT visible on a partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

	T 23 S
T 23 S	R 2 W
R 3 W	S 19
S 24	S 30
	1959

from which