

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the E. Bdy., T. 23 S., R. 3 W.

CHAINS

A fir, 55 ins. diam., bears N. $35\frac{1}{2}^{\circ}$ E., 100 lks. dist.,
mkd. T23S R2W S19 BT.

N. $1^{\circ} 13'$ E., along the E. bdy. of sec. 24, beginning new measurement.

Descend 9 ft. over NE. slope.

0.27 Creek, 3 lks. wide, course NW., curing N.; desc. 40 ft. over
NW. slope.

0.92 Same creek, course NE.; desc. 24 ft. over N. slope.

4.90 Creek, 4 lks. wide, course NE.; desc. 83 ft. over NE. slope.

13.60 Creek, 10 lks. wide, course NE.; asc. 10 ft. over SE. slope.

15.94 Top of ascent, slopes SE.; desc. 18 ft. over NE. slope.

18.20 Ravine, drains NE.; asc. 19 ft. over SE. slope.

20.02 Spur, slopes NE.; desc. 51 ft. over NE. slope.

29.80 Dry creek bed, 3 lks. wide, course NE.; asc. 36 ft. over SE. slope.

31.76 The $\frac{1}{4}$ sec. cor. of sec. 24 only, determined at record distance from
the remains of the original bearing trees:

A rotted hemlock snag, 26 ins. diam., bears S. $78\frac{1}{2}^{\circ}$ E.,
20 lks. dist., with fragmentary scribe marks visible
on old face. (Record bearing, N. 60° E.)

A rotted Hemlock snag, 18 ins. diam., bears S. $22\frac{1}{2}^{\circ}$ E.,
40 lks. dist., with scribe marks $\frac{1}{4}$ S BT on a partially
healed blaze. (Record bearing, S. 50° E., in Currin's
notes and S. 50° W., in Chandler's notes)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the
ground, with brass cap mkd.

T 23 S
R 3 W
$\frac{1}{4}$ S 24
1959

from which

A hemlock, 7 ins. diam., bears S. 38° W., 24 lks. dist.,
mkd. $\frac{1}{4}$ S24 BT.

A cedar, 8 ins. diam., bears N. $42\frac{1}{2}^{\circ}$ W., 47 lks. dist.,
mkd. $\frac{1}{4}$ S24 BT.

N. $0^{\circ} 42'$ E., beginning new measurement.

Ascend 199 ft. over SE. slope, through heavy timber and scattered
undergrowth.

8.36 Spur, slopes E.; desc. 14 ft. over NE. slope.

8.675 Point for the $\frac{1}{4}$ sec. cor. of sec. 19 only, T. 23 S., R. 2 W., at
midpoint latitudinally, on the W. bdy. of sec. 19.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground,
and in a mound of stone, 3 ft. base, to top, with brass cap mkd.