

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the S. Bdy. of T. 19 S., R. 7 W.

CHAINS

T 19 S	
R 7 W	R 6 W
S 36	S 31
T 20 S R 6 W S 6	
1949	

from which

A fir, 14 ins. diam., bears N. 44° W., 13 lks. dist.,
mkd. T19S R7W S36 BT.

S. 89° 58' W., along the S. bdy. of sec. 36, marking and blazing
the true line.

Descend 14 ft. along broken S. slope, through heavy timber and
dense undergrowth.

- 1.80 A small spur, slopes SW.; desc. 61 ft. over broken SW. slope.
- 3.85 A branch, 1 lks. wide, course S.15°W.; asc. 62 ft. over SE. slope.
- 7.60 Top of ascent on S. slope; desc. 19 ft. along broken S. slope.
- 10.05 A small spur, slopes SW.; desc. 71 ft. over broken SW. slope.
- 12.30 A branch, 2 lks. wide, course S.15°E.; asc. 373 ft. over SE. slope.
- 13.05 The closing cor. of Tps. 20 S., Rs. 6 and 7 W., bears North, 34.5 lks.
dist., monumented with the original sandstone, 20x10x8 ins. above
ground, firmly set, marked with a cross on top, CC on S. face, &
with 6 grooves on E., S., and W. faces; alongside of which is an
unmarked iron rod, $\frac{3}{4}$ " diam., welded inside the angle of an $1\frac{1}{2}$ "
angle iron, both protruding 24 ins. above ground, firmly set;
- from which the original bearing trees;
- A maple, 12 ins. diam., bears S. 86° E., 32 lks. dist., with
blaze decayed and trunk badly distorted.
- A uprooted fir, 48 ins. diam., bears S. 40° W., 30 lks. dist.,
plainly blazed and healed.
- A maple stool bears N. 7° W., 60 lks. dist. (Record 42 lks.)
- And bearing trees marked by the county surveyor:
- A fir, 60 ins. diam., bears S. 4° E., 109 lks. dist.,
marked CS T20S R6W S6 CC BT.
- A fir, 14 ins. diam., bears S. 13° W., 117 lks. dist.,
marked CS T20S R7W S1 CC BT.
- 22.50 A spur, slopes N. 85° E.; asc. 217 ft. over broken NE. slope, near
top of spur.
- 37.80 Top of mountain, from which ridges bears N., S., and W.; desc.
33 ft. along top of ridge.
- 39.67 Point for the $\frac{1}{4}$ sec. cor. of sec. 36, at proportionate distance;
there is no remaining evidence of the original corner.
- Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground,
with brass cap marked.

$\frac{1}{4}$ S 36

1949

from which