

County Surveyor's Record,³ Douglas County, Oregon

Dependent Resurvey of the S. Bdy. of T. 19 S., R. 7 W.

CHAINS

A fir, 48 ins. diam., bears N. 30° E., 18 lks. dist., marked $\frac{1}{4}$ S 36 BT.

A fir, 72 ins. diam., bears N. 77 $\frac{1}{2}$ ° W., 71 lks. dist., marked $\frac{1}{4}$ S 36 BT.

Desc. 40 ft. along top of ridge.

42.00 Leave ridge, bears E. and N. 85° W.; desc. 160 ft. over SW. slope near top of ridge.

51.05 S. side of a saddle of same ridge, bears N. 85° E. and NW.; desc. 77 ft. over broken SW. slope.

66.05 A ravine, course S. 20° E.; asc. 150 ft. over SE. slope.

75.00 Top of ascent on broken S. slope; desc. 25 ft. over broken SW. slope.

79.34 The cor. of secs. 35 and 36, determined at the record bearing from the original SW. bearing tree, and record bearing and distance from the original NW. bearing tree as follows:

A fir snag, 30 ins. diam., bears S. 75° W., 77 lks. dist., with blaze burned. (Record 65 lks. dist.)

A fir, 44 ins. diam., bears N. 20° W., 68 lks. dist., plainly blazed and healed.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked.

T 19 S R 7 W
S 35 S 36

T 20 S R 7 W
S 1
1949

from which new bearing trees

A fir, 26 ins. diam., bears N. 69° E., 48 lks. dist., marked T19S R7W S36 BT.

A fir, 32 ins. diam., bears N. 5° W., 34 lks. dist., marked T19S R7W S35 BT.

Land, mountainous.

Soil, stony clay.

Timber, fir, hemlock, maple, cedar, dogwood, chinquapin, madrona, and yew.

Undergrowth, vine maple, hazel, arrowwood salal, slickleaf, red huckleberry, and bracken.

N. 89° 38' W., along the S. bdy. of sec. 35.

Descend 65 ft. over broken SW. slope, through heavy timber and dense undergrowth.

12.34 A spur ridge, bears NE. and SW.; desc. 353 ft. over NW. slope, changing to SW. slope.

13.06 The closing corner of secs. 1 and 2, T. 20 S., R. 7 W., bears South, 8 lks. dist., monumented with a cedar post, 3 $\frac{1}{2}$ ft. long, 4 ins. square, rotted off at ground surface and partially burned, marked T20S R7W S2 and other partial marks with a scribe; and with an iron rod, $\frac{3}{4}$ " diam., welded to a 1 $\frac{1}{2}$ " angle iron, 19 ins. above ground,