

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the S. Bdy. of T. 19 S., R. 7 W.

CHAINS

A hemlock, 24 ins. diam., bears S. 40° E., 37 lks. dist., with partial scribe marks visible on face of partly open blaze.  
(Record 40 lks. dist.)

A cedar, 28 ins. diam., bears N. 25° W., 30 lks. dist., with face of blaze decayed, but partial scribe marks in negative remaining on the overgrowth.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked.

$$\begin{array}{r} T\ 19\ S\ R\ 7\ W \\ S\ 34\ |S\ 35 \\ \hline T\ 20\ S\ R\ 7\ W \\ S\ 2 \\ 1949 \end{array}$$

from which new bearing trees

A fir, 72 ins. diam., bears N. 4° E., 109 lks. dist., marked T19S R7W S35 BT.

A fir, 20 ins. diam., bears N. 33° W., 72 lks. dist., marked T19S R7W S34 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, maple, hemlock, cedar, alder, chinquapin, madrona, and cascara.

Undergrowth, vine maple, hazel, arrowwood, salal, thimbleberry, and bracken.

N. 89° 32' W., along the S. bdy. of sec. 34.

Descend 243 ft. over broken NW. slope, through heavy timber and dense undergrowth, along S. edge of logged area.

6.46 Left bank of Siuslaw River, 130 lks. wide, course S. 30° W.

7.98 Right bank of Siuslaw River; asc. 82 ft. over SE. slope.

11.52 The closing corner of secs. 2 and 3, T. 20 S., R. 7 W., bears North, 24 lks. dist., monumented with a sandstone, 20 x 18 x 8 ins., 16 ins. in the ground, marked X on top, with 2 grooves on the East face and 4 grooves on the W. face; and with an iron rod, 1½ ins. diam., 14 ins. above ground, firmly set,

from which original bearing trees

A sawed fir stump, 66 ins. diam., bears S. 12° E., 76 lks. dist., with only the base of blaze remaining.

A sawed fir stump, 66 ins. diam., bears S. 15° W., 35 lks. dist., with only the base of blaze remaining. (Record S. 10° W.)

A sawed fir stump, 40 ins. diam., bears N. 20° W., 124 lks. dist., with only the base of blaze remaining.

and trees marked by the county surveyor

A fir, 14 ins. diam., bears S. 10° E., 86 lks. dist., marked CS T20S R7W S2 CC BT.

A fir, 22 ins. diam., bears S. 66½° W., 82 lks. dist., marked CS T20S R7W S3 CC BT.

25.02 Top of broad spur, slopes S., and junction of dirt roads, extending N., S., and N. 85° E.; desc. 86 ft. over broken NW. slope.

27.40 Right bank of Siuslaw River, 100 lks. wide, course N. 15° E.