

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the S. Bdy., T. 19 S., R. 7 W.

CHAINS	
	S. 89° 57' W., along the S. bdy. of sec. 33. Descend 253 ft. over SW. slope, through heavy timber and dense undergrowth.
9.30	The closing corner of secs. 3 and 4, T. 20 S., R. 7 W., bears South, 14 lks. dist., monumented with a shattered sandstone, 16 x 12 x 8 ins., no marks remaining; and with an iron rod, 1 1/8 ins. diam., 8 ins. above ground, firmly set, from which the original bearing trees A fir, 64 ins. diam., bears N. 17° E., 75 lks. dist., plainly blazed and healed. (Record N.19°E.) A maple, 40 ins. diam., bears S. 18° E., 29 lks. dist., with old blaze healed. A cedar, 22 ins. diam., bears S. 29° W., 34 lks. dist., plainly blazed and healed. (Record S.35°W.)
9.80	A branch, 6 lks. wide, course SE.; asc. 270 ft. over broken NE. slope.
17.80	A spur, slopes NE.; asc. 110 ft. over broken NE. slope.
21.50	Top of ascent on N. slope; desc. 98 ft. over broken NW. slope.
25.80	A ravine, course NE.; asc. 390 ft. over steep NE. slope with frequent sandstone ledges.
33.00	A spur, slopes N. 10° E.; desc. 170 ft. over NW. slope.
36.75	A ravine, course N.; asc. 15 ft. over precipitous E. slope.
37.28	The 1/4 sec. cor. of sec. 33, determined at the record bearing and distance from both original bearing trees as follows: A cedar, 36 ins. diam., bears S. 81° E., 45 lks. dist., plainly blazed and healed. A fir, 28 ins. diam., bears N. 40° W., 9 lks. dist., plainly blazed and healed. At the corner point Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked $\frac{1}{4} \text{ S } 33$ 1949 from which a new bearing tree A fir, 50 ins. diam., bears N. 60° E., 80 lks. dist., marked $\frac{1}{4} \text{ S } 33 \text{ BT.}$ <hr style="width: 20%; margin: 10px auto;"/>
	S. 89° 45' W., beginning new measurement. Ascend 235 ft. over broken NE. slope.
9.85	A ridge, bears N. 60° W. and S. 60° E.; desc. 12 ft. over SW. slope.
15.55	Bottom of descent on S. slope; asc. 122 ft. over SE. slope.
28.65	Same ridge, bears N. 60° E. and S. 60° W.; asc. 4 ft. along broken N. slope.
33.55	The head of a ravine, course N. 50° E.; asc. 40 ft. over NE. slope.
34.70	A spur ridge, bears N. 5° W. and S. 5° E.; desc. 110 ft. over NW. slope.