

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the S. Bdy., T. 19 S., R. 7 W.

CHAINS							
39.40	A ravine, course N. 15° W.; asc. 10 ft. over NE. slope.						
40.00	Top of ascent on N. slope; desc. 25 ft. over broken N. slope.						
42.10	The cor. of secs. 32 and 33, monumented with the decayed remains of the original corner post, from which the original bearing trees A fir, 48 ins. diam., bears N. 78° E., 45 lks. dist., plainly blazed and healed. (Record bearing N.12°E., the complement of the actual bearing; record distance 47 lks.) A fir, 24 ins. diam., bears S.15°W., 41 lks. dist., with partial scribe marks visible on bark. (Record diam., 48 ins.; record bearing S.12°W.; record distance 45 lks.) A fir, 50 ins. diam., bears N.26°W., 14 lks. dist., plainly blazed and healed. At the corner point Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked. <div style="text-align: center;"> <table border="0"> <tr><td>T 19 S R 7 W</td></tr> <tr><td>S 32   S 33</td></tr> <tr><td>-----</td></tr> <tr><td>T 20 S R 7 W</td></tr> <tr><td>S 4</td></tr> <tr><td>1949</td></tr> </table> </div> Deposit the remains of the original post at base of iron post. Land, mountainous. Soil, stony clay. Timber, fir, hemlock, maple, cedar, dogwood; madrona, and chinquapin. Undergrowth, vine maple, arrowwood, hazel, slickleaf, poison oak, salal, salmonberry, huckleberry, and bracken.	T 19 S R 7 W	S 32   S 33	-----	T 20 S R 7 W	S 4	1949
T 19 S R 7 W							
S 32   S 33							
-----							
T 20 S R 7 W							
S 4							
1949							
	S. 89° 57' W., along the S. bdy. of sec. 32. Descend 101 ft. along N. slope, changing to NW. slope, through heavy timber and dense undergrowth.						
4.20	A branch, 3 lks. wide, course N. 20° E.; asc. 231 ft. over NE. slope.						
8.32	The closing corner of secs. 4 and 5, T. 20 S., R. 7 W., bears North, 3 lks. dist., monumented with a sandstone, 18x10x8 ins., 12 ins. above ground, marked X on top, CC on N. face, with 2 grooves on W. face and 4 grooves on E. face; and with an iron bar, 1 in. diam., 20 ins. above ground, firmly set, from which the original bearing trees A fir, 60 ins. diam., bears N. 24° E., 22 lks. dist., plainly blazed and healed. (Record distance 74 lks.) A fir, 52 ins. diam., bears S. 78° E., 89 lks. dist., with blaze partially exposed and decayed. (Record bearing S. 70° E., 100 lks. dist.) A fir, 54 ins. diam., bears S. 8° W., 43 lks. dist., plainly blazed and healed.						
10.05	Top of mountain; spur ridges bear N. 30° E. and W.; desc. 12 ft. along high, rolling ridgetop.						
13.95	Leave spur ridge, bears E. and NW.; desc. 218 ft. over SW. slope, changing to W. slope.						