

County Surveyor's Record, Douglas County, Oregon

CHAINS	
21.45	A branch, 2 lks. wide, course N. 10° W.; asc. 18 ft. over NE. slope.
22.40	A small spur, slopes N.; desc. 2 ft. over NW. slope.
23.00	A branch, 1 lk. wide, course N. 15° E.; asc. 125 ft. over E. slope.
27.50	A ridge, bears N. and S.; desc. 254 ft. over precipitous W. slope.
31.95	A ravine, course NW.; desc. 170 ft. along N. slope, changing to N.W. slope.
39.25	The $\frac{1}{4}$ sec. cor. of sec. 32, monumented with a sandstone, 16x16x12 ins. firmly set, marked $\frac{1}{4}$ S on N. face and with a cross on top, from which the original bearing trees, A fir, 55 ins. diam., bears S.10°E., 50 lks. dist., with blaze healed, but overgrowth partially burned. (Record S. 20° E., 35 lks. dist.) A fir, 28 ins. diam., bears N. 30° W., 10 lks. dist., plainly blazed and healed. At the corner point Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked $\frac{1}{4} S 32$ <hr/> 1949 from which a new bearing tree A fir, 40 ins. diam., bears N. 59° E., 105 lks. dist., marked $\frac{1}{4}$ S32 BT. Deposit original stone at base of iron post. <hr/> S. 89° 57' W., beginning new measurement. Descend 169 ft. over NW. slope, changing to precipitous W. slope.
3.30	The dry bed of a stream, 4 lks. wide, course N.; asc. 316 ft. over steep E. slope.
9.20	A spur, slopes N. 40° E.; desc. 113 ft. over NW. slope.
13.80	A ravine, course N. 30° E.; asc. 226 ft. over steep E. slope.
18.40	A spur, slopes N.; desc. 266 ft. over steep NW. slope.
23.85	A branch, 1 lk. wide, course N. 10° E.; asc. 367 ft. over steep E. slope.
31.35	A spur, slopes N.; desc. 90 ft. over NW. slope, changing to broken N. slope.
35.35	A spur, slopes NW.; desc. 264 ft. over broken NW. slope.
40.30	The dry bed of a stream, 4 lks. wide, course N.; asc. 3 ft. over NE. slope.
40.41	The cor. of secs. 31 and 32, monumented with a disintegrating sandstone, 20x18x10 ins., firmly set, with only partial chisel marks remaining. At the corner point Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked.