

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the S. Bdy., T. 19 S., R. 7 W.

CHAINS

T 19 S R 7 W
S 31   S 32

T 20 S R 7 W

S 5

1949

from which new bearing trees

A fir, 26 ins. diam., bears N.  $82^{\circ} 45'$  E., 71 lks. dist., mkd. T19S R7W S32 BT.

A fir, 20 ins. diam., bears N.  $13\frac{1}{2}^{\circ}$  W., 91 lks. dist., marked T19S R7W S31 BT.

Deposit the sandstone at the base of the iron post.

Land, mountainous.

Soil, rocky clay.

Timber, fir, maple, chinquapin, hemlock, cedar, alder, and madrona.

Undergrowth, vine maple, hazel, arrowwood, slickleaf, manzanita, salal, huckleberry, poison oak, and bracken.

N.  $89^{\circ} 19'$  W., along the S. bdy. of sec. 31

Ascend 311 ft. over NE. slope, changing to steep E. slope, through heavy timber and dense undergrowth.

5.35 A spur, slopes N.  $15^{\circ}$  E.; desc. 211 ft. over NW. slope.

8.90 The closing corner of secs. 5 and 6, T. 20 S., R. 7 W., bears North, 17 lks. dist., monumented with a sandstone, 12x10x6 ins. above ground, firmly set, marked with a cross on top, C C on N. face, & with 1 groove on W. face; and with an iron rod,  $\frac{3}{4}$  in. diam., welded to a  $1\frac{1}{2}$ " angle iron, 24 ins. above ground, firmly set,

from which original bearing trees

A fir snag, 50 ins. diam., bears N.  $28^{\circ}$  E., 98 lks. dist., plainly blazed and healed. (Record bearing N.  $30^{\circ}$  E.)

A splintered fir stump, 48 ins. diam., bears S.  $78^{\circ}$  E., 21 lks. dist., with partial scribe marks visible on fallen trunk. (Record distance 27 lks.)

and trees marked by the county surveyor

A fir, 7 ins. diam., bears S.  $83\frac{1}{4}^{\circ}$  E., 13 lks. dist., marked CS T20S R7W S5 CC BT.

A fir, 7 ins. diam., bears S.  $37\frac{1}{4}^{\circ}$  W., 18 lks. dist., marked CS T20S R7W S6 CC BT.

11.15 The head of a ravine, course N.  $40^{\circ}$  W.; asc. 6 ft. over NE. slope.

11.90 A small spur, slopes NW.; desc. 67 ft. over NW. slope.

13.90 A ravine, course NE.; asc. 421 ft. over SE. slope, changing to steep E. slope.

22.25 A spur, slopes NE.; asc. 70 ft. along broken N. slope, changing to NE. slope.

25.55 A ridge, bears N.  $10^{\circ}$  W. and S.  $10^{\circ}$  E.; desc. 160 ft. over W. slope.32.90 A branch, 2 lks. wide, course S.  $20^{\circ}$  W.; asc. 80 ft. over SE. slope.

38.19 The  $\frac{1}{4}$  sec. cor. of sec. 31, determined at the record bearing from the original SE. bearing tree and at the record bearing and distance from the original NW. bearing tree, as follows: