

County Surveyor's Record, Douglas County, Oregon

18614

Retracement of South Boundary of T. 29 S., R. 9 W.

CHAINS

~~A fir, 60 ins. in diam. bears N. 31° E. 93 lks. dist. Mkd:
T 29 S R 9 W S 31 B T~~

~~Thence from this corner established by me for S.W. corner of
FROM THE CORNER ESTABLISHED BY DEPUTY WRIGHT AS
Tp. 29 S., R. 9 W., I run N. on blank line on W. sec. 31 after
CORNER FOR Twp. 29 + 30 SOUTH, RANGES 10 WEST SUBSEQUENTLY
destroying the markings on the two old corners referring to
CHANGED BY ME FOR CORNER T. 29 S. R. 9 + 10 W. ON N. Bdy. of Sec. 1
T. 29 S. R. 9 W. T30 R 10 W.~~

North on blank line on W. bdy. of sec. 31.

~~2.00~~ Tp. corner set by Deputy Wright

Gradual ascent through old burn with scattering timber and dense undergrowth.

~~40.00~~
33.00

Set a Cedar post 3 feet long 4 ins. square 24 ins. in ground, for the $\frac{1}{4}$ sec. cor. for sec. 31, marked:

+ + + + +
+ + + + +

SUPPLEMENTARY FIELD NOTES TO SURVEYS EXECUTED UNDER CONTRACT
NO. 768, by Wm. M. Porter, Deputy Surveyor.

Complying with instructions contained in letter "E", dated April 29, 1909, from the Hon. Commissioner of the General Land Office, on July 16, 1909, I returned to the field, and have made the following amendments in connection with my surveys in T. 29 S., R. 9 W., under special instructions, dated June 5, 1907, independent of, but in connection with my contract No. 768, dated March 8, 1907, viz:

As the cor. of Tps. 29 and 30 S., R. 9 W., on the E bdy., Sec. 1, T. 30 S., R. 10 W., established by Deputy Hathorn, under contract No. 57, as common to four townships, cannot properly refer to the township on the west, I obliterate the markings on the SW. and NW. bearing trees for this corner and change the markings on corner stone to read as follows:
T 29 S on N., R 9 W on E., and
T 30 S on S. face; with 6 notches on S. & E. edges.

At this point, July 16, 1909, I set solar compass at 1 p.m., l.m.t., and set off 43° on the lat. arc; and 21° 25' N. on the decl. arc, and observe the sun for the meridian.

2.00 Thence I run North
Set basalt stone, 22 x 17 x 6 ins., 16 $\frac{1}{2}$ ins. in the ground, for NE. cor. sec. 1, T. 30 S., R. 10 W., marked with 6 notches on S. and W. edges; from which:

A Myrtle Tree, 4 ins. diam., bears S. 64° W., 15 lks. dist., marked: T30 S R 10 W S 1 B T.

I destroy the erroneous corner, formerly established by me, 2.00 chs. S. of the cor. of Tps. 29 S., Rs. 9 and 10 W., on N. bdy. sec. 1, T. 30 S., R. 10 W., and 2.08 chs. west of cor. of Tps. 29 and 30 S., Rs. 9 W., on E. bdy. of said sec. 1, and obliterate the markings on the bearing tree referring to this erroneous corner.

2.08 From the said N.E. cor. of sec. 1, I run West,
To Cor. of Tps. 29 S., Rs. 9 & 10 W. on N. bdy., sec. 1, T. 30 S., R. 10 W., established by Deputy Wright, under cont. #358. In place of the post formerly set, I set a basalt stone, 20 x 17 x 4 ins., 15 ins. in the ground, at corner point, marked:
T. 29 S on N., R 9 W on E. and R 10 W on W. face with 6 notches on N. and W. edges.

I obliterate the marks on the SW. and SE. bearing trees for this corner.