

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the W. Bdy., T. 19 S., R. 8 W.

CHAINS	Ascend 145 ft. over SE. slope, changing to S. slope, through heavy timber and dense undergrowth.								
6.40	Ridge, bears E. and W.; desc. 500 ft. over broken NW. slope.								
18.145	Point for the S 1/16 sec. cor. of sec. 36 only, on the E. bdy. of T. 19 S., R. 9 W.  Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td style="padding-right: 5px;">S 1/16</td><td style="border-left: 1px solid black; padding-left: 5px;"> </td></tr> <tr><td style="padding-right: 5px;">S 36</td><td style="border-left: 1px solid black; padding-left: 5px;"> </td></tr> <tr><td style="padding-right: 5px;"></td><td style="border-left: 1px solid black; padding-left: 5px;"> </td></tr> <tr><td style="padding-right: 5px;"></td><td style="border-left: 1px solid black; padding-left: 5px;">1957</td></tr> </table> </div>	S 1/16		S 36					1957
S 1/16									
S 36									
	1957								
	from which  <div style="margin-left: 40px;"> <p>A maple, 10 ins. diam., bears West, <math>42\frac{1}{2}</math> lks. dist., mkd. S 1/16 S36 BT.</p> <p>A maple, 22 ins. diam., bears S. <math>64^\circ</math> W., 85 lks. dist., mkd. S 1/16 S36 BT.</p> </div>								
	Descend 16 ft. over NW. slope.								
18.55	Branch, 4 lks. wide, course N. $30^\circ$ E.; desc. 65 ft. over broken NE. slope.								
22.85	Right bank of the West Fork of Smith River, course S. $70^\circ$ E.								
23.50	Left bank of the West Fork; asc. 185 ft. over SW. slope.								
38.31	Point for the $\frac{1}{4}$ sec. cor. of sec. 36 only, on the E. bdy. of T. 19 S., R. 9 W., at midpoint between closing corners.  Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td style="padding-right: 5px;">T 19 S</td><td style="border-left: 1px solid black; padding-left: 5px;"> </td></tr> <tr><td style="padding-right: 5px;"><math>\frac{1}{4}</math> S 36</td><td style="border-left: 1px solid black; padding-left: 5px;"> </td></tr> <tr><td style="padding-right: 5px;">R 9 W</td><td style="border-left: 1px solid black; padding-left: 5px;"> </td></tr> <tr><td style="padding-right: 5px;"></td><td style="border-left: 1px solid black; padding-left: 5px;">1957</td></tr> </table> <div style="margin-left: 100px; font-size: small; font-style: italic;"> <p>FD OK 6/5/81 2080 FT'S L. N. 87.78</p> </div> </div>	T 19 S		$\frac{1}{4}$ S 36		R 9 W			1957
T 19 S									
$\frac{1}{4}$ S 36									
R 9 W									
	1957								
	from which  <div style="margin-left: 40px;"> <p>A fir, 22 ins. diam., bears N. <math>22^\circ</math> W., 13 lks. dist., mkd. <math>\frac{1}{4}</math> S36 BT.</p> <p>A fir, 8 ins. diam., bears S. <math>47^\circ</math> W., 83 lks. dist., mkd. <math>\frac{1}{4}</math> S36 BT.</p> </div>								
	Ascend 24 ft. over SW. slope.								
40.63	The corner of secs. 30 and 31 only, marked by the remains of the original corner tree; a rotted fir stump, 24 ins. diam., from which the original bearing trees:  <div style="margin-left: 40px;"> <p>A fir, 16 ins. diam., bears N. <math>70^\circ</math> E., 26 lks. dist., with scribe marks 19S E8W S30 visible on opened and partly healed blaze. (Record bearing, N. <math>66\frac{1}{2}^\circ</math> E.)</p> <p>A fir, 25 ins. diam., bears S. <math>40^\circ</math> E., 24 lks. dist., with a healed blaze. (Record bearing, S. <math>40\frac{1}{2}^\circ</math> E.)</p> </div>								
	At the corner point, through stump of corner tree,  Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.								