

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the W. Bdy. of T. 19 S., R. ⁸/₃ W.

CHAINS

T 19 S T 19 S
 S 36 | S 30
 | S 31
 R 9 W R 8 W
 1957

*FD OK 6/15/81
 L. ROBERTS
 M 87-78*

from which a new bearing tree:

a fir, 20 ins. diam., bears N. $4\frac{3}{4}^{\circ}$ E., 46 lks. dist.,
 mkd. T19S R8W S30 BT.

Land, mountainous.
 Soil, sandy clay loam.
 Timber, fir, hemlock, cedar, maple and alder.
 Undergrowth, vine maple, salmonberry, evergreen huckleberry,
 hazel and arrowwood.

N. $0^{\circ} 11'$ E., along the W. bdy. of sec. 30.

Descend 185 ft. over W. slope, changing to broken NW. slope,
 through heavy timber and dense undergrowth.

13.95 West Fork of Smith River, 30 lks. wide, course W.; asc. 15 ft.
 over S. slope.

17.845 Point for the N 1/16 sec. cor. of sec. 36 only, on the E. bdy.
 of T. 19 S., R. 9 W.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground,
 with brass cap mkd.

N 1/16 |
 S 36 |
 1957

*FD OK 6/15/81
 L. ROBERTS
 M 87-78*

from which

A fir, 17 ins. diam., bears N. $64\frac{1}{4}^{\circ}$ W., 51 lks. dist.,
 mkd. N 1/16 S36 BT.

A hemlock, 8 ins. diam., bears S. 81° W., 36 lks. dist.,
 mkd. N 1/16 S36 BT.

Ascend 28 ft. over S. slope.

20.16 Point for the S 1/16 sec. cor. of sec. 30 only.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground,
 with brass cap mkd.

| S 1/16
 | S 30
 1957

*FD OK 6/15/81
 L. ROBERTS
 M 87-78*

from which

A fir, 6 ins. diam., bears N. 51° E., 25 lks. dist.,
 mkd. S 1/16 S30 BT.

A fir, 9 ins. diam., bears S. $7\frac{1}{4}^{\circ}$ E., 25 lks. dist.,
 mkd. S 1/16 S30 BT.

Ascend 245 ft. over S. slope, changing to SE. slope.

38.01 Point for the closing cor. of secs. 25 and 36, T. 19 S., R. 9 W.,
 at proportionate distance; there is no remaining evidence of the
 original corner.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground,
 with brass cap mkd.