

County Surveyor's Record, Douglas County, Oregon

-4-

Dependent Resurvey of a Portion of the W. Bdy. of T. 19 S., R. 8 W.

CHAINS

T 19 S | T 19 S
 CC S 25 | S 30
 S 36 |
 R 9 W | R 8 W
 1957

*FD OK 6/5/81
 L. ROBERTS
 M87-78*

from which

A fir, 40 ins. diam., bears N. 75° W., 28 lks. dist.,
 mkd. T19S R9W S25 CC BT.

A fir, 26 ins. diam., bears S. 71° W., 88 lks. dist.,
 mkd. T19S R9W S36 CC BT.

Ascend 40 ft. over SE. slope.

40.32 The 1/4 sec. cor. of sec. 30 only, determined from the original bearing trees:

A maple, 20 ins. diam., bears N. 36 1/4° E., 92 lks. dist.,
 with no scribe marks visible on opened blaze. (Record bearing, N. 33 3/4° E., distance omitted in orig. notes)

A sawed fir stump, 48 ins. diam., bears S. 20 1/2° W., 66 lks. dist., with scribe marks scaled off distinct bark blaze.

At the corner point.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T 19 S
 1/4 S 30
 R 8 W
 1957

*FD OK 6/5/81
 L. ROBERTS
 M87-78*

from which new bearing trees:

A maple, 15 ins. diam., bears N. 48 3/4° E., 36 lks. dist.,
 mkd. 1/4 S30 BT.

A hemlock, 20 ins. diam., bears S. 11 3/4° E., 18 lks. dist.,
 mkd. 1/4 S30 BT.

N. 0° 24 ' W., beginning new measurement.

Ascend 310 ft. over S. slope.

17.55 Top of ascent, slopes E.; desc. 380 ft. over general N. slope.

28.70 Branch, 3 lks. wide, course N. 20° E.; desc. 75 ft. along broken slope.

31.95 Branch, 2 lks. wide, course NE.; asc. 50 ft. over SE. slope.

34.50 Top of ascent, slopes E.; desc. 125 ft. over N. slope.

37.25 Creek, 10 lks. wide, course S. 75° E.; asc. 50 ft. over SW. slope.

38.25 Point for the 1/4 sec. cor. of sec. 25 only, on the E. bdy of T. 19 S., R. 9 W., at midpoint between closing corners.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T 19 S
 1/4 S 25
 R 9 W
 1957

*FD OK 6/5/81
 L. ROBERTS
 M87-78*

from which