

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the W. Bdy. of T. 19 S., R. 8 W.

CHAINS

A maple, 18 ins. diam., bears N. 75° W., 28 lks. dist., mkd. ¼ S25 BT.

A maple, 18 ins. diam., bears S. 56° W., 41 lks. dist., mkd. ¼ S25 BT.

Ascent 55 ft. over SW. slope.

41.14 The cor. of secs. 19 and 30 only, in the stump hole of an uprooted maple, 18 ins. diam., with no marks remaining, determined at the intersection of the original plainly blazed lines; from which an original bearing tree is as follows:

A maple, 14 ins. diam., bears N. 27° E., 29 lks. dist., with no scribe marks visible on opened blaze. (Record bearing, N. 57° E.)

At the corner point.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T 19 S | T 19 S
S 19
S 30
R 9 W | R 8 W
1957

Fd. ok 6/5/81 L. Rogers MSB-78

from which new bearing trees:

A maple, 15 ins. diam., bears N. 81½° E., 56½ lks. dist., mkd. T19S R8W S19 BT.

A maple, 14 ins. diam., bears S. 16½° E., 9 lks. dist., mkd. T19S R8W S30 BT.

The corner is located 10 lks. W. of a branch, 4 lks. wide, course S.

Land, mountainous.
Soil, sandy clay loam.
Timber, fir hemlock, cedar, maple, alder, cascara and yew.
Undergrowth, vine maple, salmonberry, evergreen huckleberry, red huckleberry, hazel, arrowwood, ceanothus.

N. 0° 25' W., along the W. bdy. of sec. 19.

Ascend 465 ft. over S. slope, through heavy timber and dense undergrowth.

26.60 Top of ascent, slopes E.; desc. 20 ft. over NE. slope.

37.40 Ravine, course S. 80° E.; asc. 8 ft. over S. slope.

37.67 Point for the closing cor. of secs. 24 and 25, T. 19 S., R. 9 W., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T 19 S | T19 S
CC S 24 | S 19
S 25
R 9 W | R 8 W
1957

from which

An alder, 10 ins. diam., bears N. 76½° W., 57 lks. dist., mkd. T19S R9W S24 CC BT.