

## County Surveyor's Record, Douglas County, Oregon

-6-

Dependent Resurvey of a Portion of the W. Bdy. of T. 19 S., R. 8 W

CHAINS

An alder, 16 ins. diam., bears S.  $33\frac{1}{2}^{\circ}$  W., 17 lks. dist.,  
mkd. T19S R9W S25 CC BT.

Ascend 10 ft. over S. slope.

38.40 Spur, slopes S.  $80^{\circ}$  E.; desc. 20 ft. over NE. slope.

39.90 Point for the  $\frac{1}{4}$  sec. cor. of sec. 19 only, at proportionate distance;  
there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground,  
with brass cap mkd.

T 19 S  
 $\frac{1}{4}$  S 19  
R 8 W

1957

from which

A fir, 24 ins. diam., bears N.  $26\frac{1}{2}^{\circ}$  E., 55 lks. dist.,  
mkd.  $\frac{1}{4}$  S19 BT.

An alder, 8 ins. diam., bears S.  $37\frac{1}{2}^{\circ}$  E., 13 lks. dist.,  
mkd.  $\frac{1}{4}$  S19 BT.

Descend 150 ft. over NE. slope.

49.70 Spring branch, 1 lk. wide, course NE.; desc. 165 ft. over NE. slope,  
changing to N. slope.

54.50 Bottom of steep N. slope, bears E. and W.; thence across bottom land.

55.60 Creek, 15 lks. wide, course N.  $80^{\circ}$  E.; continue over bottom land.

57.845 Point for the S  $\frac{1}{16}$  sec. cor. of sec. 24 only, on the E. bdy. of  
T 19 S., R. 9 W.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground,  
with brass cap mkd.

S  $\frac{1}{16}$  |  
S 24 |  
1957

from which

An alder, 20 ins. diam., bears N.  $20^{\circ}$  W., 107 lks. dist.,  
mkd. S  $\frac{1}{16}$  S24 BT.

A double maple, 24 ins. diam., bears S.  $60^{\circ}$  W., 92 lks. dist.,  
mkd. S  $\frac{1}{16}$  S24 BT.

Continue over bottom land.

58.60 West Fork of Smith River, 10 lks. wide, course S.  $75^{\circ}$  E.; asc.  
15 ft. along W. slope.

66.00 West Fork of Smith River, 10 lks. wide, course SW.; asc.  
gradually over bottom land.

72.60 West Fork of Smith River, 8 lks. wide, course S.  $20^{\circ}$  E.; asc.  
45 ft. over SW. slope.

78.02 Point for the  $\frac{1}{4}$  sec. cor. of sec. 24 only, on the E. bdy. of  
T. 19 S., R. 9 W., at midpoint between closing corners.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground,  
with brass cap mkd.